



FFA.2E.310.CLAC65 Information

Heisener.com

Part Number FFA.2E.310.CLAC65

Manufacturer LEMO

Category Connectors, Interconnects

Circular Connectors

Description CONN INLINE PLUG 10POS SLD CUP

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FFA.2E.310.CLAC65 Specifications

Manufacturer Part NumberFFA.2E.310.CLAC65ManufacturerLEMOCategoryConnectors, Interconnects Circular ConnectorsPackage-Series2EConnector TypePlug, Female Sockets and Male PinsNumber of Positions10Shell Size - Insert310Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating7A		
CategoryConnectors, InterconnectsPackage-Series2EConnector TypePlug, Female Sockets and Male PinsNumber of Positions10Shell Size - Insert310Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating7A	Manufacturer Part Number	FFA.2E.310.CLAC65
Package-Series2EConnector TypePlug, Female Sockets and Male PinsNumber of Positions10Shell Size - Insert310Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating7A	Manufacturer	LEMO
Package-Series2EConnector TypePlug, Female Sockets and Male PinsNumber of Positions10Shell Size - Insert310Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating7A	Category	Connectors, Interconnects
Series2EConnector TypePlug, Female Sockets and Male PinsNumber of Positions10Shell Size - Insert310Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating7A		Circular Connectors
Connector TypePlug, Female Sockets and Male PinsNumber of Positions10Shell Size - Insert310Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating7A	Package	-
Number of Positions10Shell Size - Insert310Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating7A	Series	2E
Shell Size - Insert 310 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Push-Pull Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated - Current Rating 7A	Connector Type	Plug, Female Sockets and Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Push-Pull Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated - Current Rating 7A	Number of Positions	10
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating7A	Shell Size - Insert	310
Termination Solder Cup Fastening Type Push-Pull Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated Current Rating 7A	Shell Size, MIL	-
Fastening Type Push-Pull Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated - Current Rating 7A	Mounting Type	Free Hanging (In-Line)
Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated - Current Rating 7A	Termination	Solder Cup
Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Contact Finish Gold Features Backshell, Shielded Voltage - Rated - Current Rating 7A	Fastening Type	Push-Pull
Shell Material, Finish Contact Finish Gold Features Backshell, Shielded Voltage - Rated - Current Rating 7A	Orientation	Keyed
Contact Finish Gold Features Backshell, Shielded Voltage - Rated - Current Rating 7A	Ingress Protection	IP66/68 - Dust Tight, Water Resistant, Waterproof
Features Backshell, Shielded Voltage - Rated - Current Rating 7A	Shell Material, Finish	Brass, Chrome Plated
Voltage - Rated - Current Rating 7A	Contact Finish	Gold
Current Rating 7A	Features	Backshell, Shielded
-	Voltage - Rated	-
Report errors?	Current Rating	7A
		Report errors

FFA.2E.310.CLAC65 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FFA.2E.310.CLAC65 Payment Methods



















FFA.2E.310.CLAC65 Shipping Methods













If you have any question about FFA.2E.310.CLAC65, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com