



FFA.2S.310.CLAC72 Information

Heisener.com

Part Number FFA.2S.310.CLAC72

Manufacturer LEMO

Category Connectors, Interconnects

Circular Connectors

Description CONN INLINE PLUG 10PIN SLD CUP

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FFA.2S.310.CLAC72 Specifications

Manufacturer Part Number FFA.2S.310.CLAC72 Manufacturer LEMO Category Connectors, Interconnects Package - Series 2S Connector Type Plug, Female Sockets and Male Pins Number of Positions 10 Shell Size - Insert 310 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated - Current Rating 7A		
CategoryConnectors, InterconnectsPackage-Series2SConnector TypePlug, Female Sockets and Male PinsNumber of Positions10Shell Size - Insert310Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-Pull, Detent LockOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating7A	Manufacturer Part Number	FFA.2S.310.CLAC72
Package-Series2SConnector TypePlug, Female Sockets and Male PinsNumber of Positions10Shell Size - Insert310Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-Pull, Detent LockOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating7A	Manufacturer	LEMO
Package-Series2SConnector TypePlug, Female Sockets and Male PinsNumber of Positions10Shell Size - Insert310Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-Pull, Detent LockOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating7A	Category	Connectors, Interconnects
Series2SConnector TypePlug, Female Sockets and Male PinsNumber of Positions10Shell Size - Insert310Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-Pull, Detent LockOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating7A		Circular Connectors
Connector Type Plug, Female Sockets and Male Pins Number of Positions 10 Shell Size - Insert 310 Shell Size, MIL	Package	-
Number of Positions10Shell Size - Insert310Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-Pull, Detent LockOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating7A	Series	2S
Shell Size - Insert Shell Size, MIL	Connector Type	Plug, Female Sockets and Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated - Current Rating 7A	Number of Positions	10
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-Pull, Detent LockOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating7A	Shell Size - Insert	310
Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated Current Rating 7A	Shell Size, MIL	-
Fastening Type Push-Pull, Detent Lock Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated - Current Rating 7A	Mounting Type	Free Hanging (In-Line)
Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated Current Rating 7A	Termination	Solder Cup
Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated - Current Rating 7A	Fastening Type	Push-Pull, Detent Lock
Shell Material, Finish Contact Finish Gold Features Backshell, Shielded Voltage - Rated Current Rating 7A	Orientation	Keyed
Contact Finish Gold Features Backshell, Shielded Voltage - Rated - Current Rating 7A	Ingress Protection	IP50 - Dust Protected
Features Backshell, Shielded Voltage - Rated - Current Rating 7A	Shell Material, Finish	Brass, Chrome Plated
Voltage - Rated - Current Rating 7A	Contact Finish	Gold
Current Rating 7A	Features	Backshell, Shielded
	Voltage - Rated	-
Report errors?	Current Rating	7A
		Report errors?

FFA.2S.310.CLAC72 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FFA.2S.310.CLAC72 Payment Methods





















FFA.2S.310.CLAC72 Shipping Methods













If you have any question about FFA.2S.310.CLAC72, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com