

FFA.3E.306.CLAC11

FFA.3E.306.CLAC11 Information

| Heisener.com | Part Number Manufacturer Category Description Package | FFA.3E.306.CLAC11 LEMO Connectors, Interconnects Circular Connectors CONN INLINE PLUG 6PIN SLD CUP - For the pricing/inventory/lead time, please contact | |
|--------------------|---|--|-----------------|
| For Reference Only | | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



FFA.3E.306.CLAC11 Specifications

| ManufacturerLEMOCategoryConnectors, InterconnectsCircular ConnectorsPackage-Series3EConnector TypePlug, Female Sockets and Male PinsNumber of Positions6Shell Size - Insert306Shell Size, MIL-Mounting TypeFree Hanging (In-Line)FerminationSolder CupFastening TypeUsh-PullOrientationKeyedShell Material, FinishBrass, Chrome PlatedShell Material, FinishGoldFeaturesBackshell, ShieldedVoltage - Rated- | | |
|---|--------------------------|---|
| CategoryConnectors, Interconnects Circular ConnectorsPackage-Package3EConnector TypePlug, Female Sockets and Male PinsConnector Type6Shell Size - Insert306Shell Size, MIL-Munting TypeFree Hanging (In-Line)ForminationSolder CupPatening TypeUsh-PullOrientationKeyedShell Material, FinishBrass, Chrome PlatedShell Material, FinishGoldFeaturesGoldVoltage - Rated-Voltage - Rated14A | Manufacturer Part Number | FFA.3E.306.CLAC11 |
| Circular ConnectorsPackage-Series3EConnector TypePlug, Female Sockets and Male PinsNumber of Positions6Shell Size - Insert306Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating14A | Manufacturer | LEMO |
| Package-Series3EConnector TypePlug, Female Sockets and Male PinsNumber of Positions6Shell Size - Insert306Shell Size, MIL-Mounting TypeFree Hanging (In-Line)FerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionBr66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldVoltage - Rated-Current Rating14A | Category | Connectors, Interconnects |
| Series3EConnector TypePlug, Female Sockets and Male PinsNumber of Positions6Shell Size - Insert306Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionPf66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishGoldContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating14A | | Circular Connectors |
| Connector TypePlug, Female Sockets and Male PinsNumber of Positions6Shell Size - Insert306Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionBress, Chrome PlatedShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Kurrent Rating14A | Package | - |
| Number of Positions6Shell Size - Insert306Shell Size, MIL-Mounting TypeFree Hanging (In-Line)Mounting TypeSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating14A | Series | 3E |
| Shell Size - Insert306Shell Size, MIL-Mounting TypeFree Hanging (In-Line)Mounting TypeSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated14A | Connector Type | Plug, Female Sockets and Male Pins |
| Shell Size, MIL-Mounting TypeFree Hanging (In-Line)FerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Lurrent Rating14A | Number of Positions | 6 |
| Mounting TypeFree Hanging (In-Line)FerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Kurent Rating14A | Shell Size - Insert | 306 |
| TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Lurent Rating14A | Shell Size, MIL | - |
| Fastening TypePush-PullOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating14A | Mounting Type | Free Hanging (In-Line) |
| OrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating14A | Termination | Solder Cup |
| Ingress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating14A | Fastening Type | Push-Pull |
| Shell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating14A | Orientation | Keyed |
| Contact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating14A | Ingress Protection | IP66/68 - Dust Tight, Water Resistant, Waterproof |
| FeaturesBackshell, ShieldedVoltage - Rated-Current Rating14A | Shell Material, Finish | Brass, Chrome Plated |
| Voltage - Rated-Current Rating14A | Contact Finish | Gold |
| Current Rating 14A | Features | Backshell, Shielded |
| - | Voltage - Rated | - |
| Report errors? | Current Rating | 14A |
| | | Report errors? |

FFA.3E.306.CLAC11 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

FFA.3E.306.CLAC11 Payment Methods



FFA.3E.306.CLAC11 Shipping Methods



If you have any question about FFA.3E.306.CLAC11, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com