

FFP20UP20DNTU

FFP20UP20DNTU Information

www.helsens.com	 FFP20UP20DNTU Fairchild/ON Semiconductor Discrete Semiconductor Products Diodes - Rectifiers - Arrays DIODE ARRAY GP 200V 10A TO220 TO-220-3 For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



FFP20UP20DNTU Specifications

Manufacturer Fairchild/ON Semiconductor Category Discrete Semiconductor Products Diodes - Rectifiers - Arrays Diodes - Rectifiers - Arrays Package TO-220-3 Series - Diode Configuration 1 Pair Common Cathode Diode Type Standard Voltage - DC Reverse (Vr) (Max) 200V Current - Average Rectified (Io) (per Diode) 10A Voltage - Forward (Vf) (Max) @ If 1.15V @ 10A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 45ns Current - Reverse Leakage @ Vr 100µA @ 200V Operating Temperature - Junction -65°C ~ 150°C Mounting Type Through Hole Package / Case TO-220-3		
CategoryDiscrete Semiconductor ProductsCategoryDiscrete Semiconductor ProductsPackageDiodes - Rectifiers - ArraysPackageTO-220-3Series-Diode Configuration1 Pair Common CathodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)200VCurrent - Average Rectified (Io) (per Diode)10AVoltage - Forward (Vf) (Max) @ If1.15V @ 10ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)45nsCurrent - Reverse Leakage @ Vr100µA @ 200VOperating Temperature - Junction-65°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220	Manufacturer Part Number	FFP20UP20DNTU
Diodes - Rectifiers - ArraysPackageDiodes - Rectifiers - ArraysPackageTO-220-3Series-Diode Configuration1 Pair Common CathodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)200VCurrent - Average Rectified (Io) (per Diode)10AVoltage - Forward (Vf) (Max) @ If1.15V @ 10ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)45nsCurrent - Reverse Leakage @ Vr100µA @ 200VOperating Temperature - Junction-65°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220	Manufacturer	Fairchild/ON Semiconductor
Package TO-220-3 Series - Diode Configuration 1 Pair Common Cathode Diode Type Standard Voltage - DC Reverse (Vr) (Max) 200V Current - Average Rectified (Io) (per Diode) 10A Voltage - Forward (Vf) (Max) @ If 1.15V @ 10A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 45ns Current - Reverse Leakage @ Vr 100μA @ 200V Operating Temperature - Junction -65°C ~ 150°C Mounting Type Through Hole Package / Case TO-220-3	Category	Discrete Semiconductor Products
Series - Diode Configuration 1 Pair Common Cathode Diode Type Standard Voltage - DC Reverse (Vr) (Max) 200V Current - Average Rectified (Io) (per Diode) 10A Voltage - Forward (Vf) (Max) @ If 1.15V @ 10A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 45ns Current - Reverse Leakage @ Vr 100µA @ 200V Operating Temperature - Junction -65°C ~ 150°C Mounting Type Through Hole Package / Case TO-220-3		Diodes - Rectifiers - Arrays
Diode Configuration1 Pair Common CathodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)200VCurrent - Average Rectified (Io) (per Diode)10AVoltage - Forward (Vf) (Max) @ If1.15V @ 10ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)45nsCurrent - Reverse Leakage @ Vr100µA @ 200VOperating Temperature - Junction-65°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220	Package	TO-220-3
Diode TypeStandardDiode TypeStandardVoltage - DC Reverse (Vr) (Max)200VCurrent - Average Rectified (Io) (per Diode)10AVoltage - Forward (Vf) (Max) @ If1.15V @ 10ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)45nsCurrent - Reverse Leakage @ Vr100µA @ 200VOperating Temperature - Junction-65°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220	Series	-
Voltage - DC Reverse (Vr) (Max)200VCurrent - Average Rectified (Io) (per Diode)10AVoltage - Forward (Vf) (Max) @ If1.15V @ 10ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)45nsCurrent - Reverse Leakage @ Vr100µA @ 200VOperating Temperature - Junction-65°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220	Diode Configuration	1 Pair Common Cathode
Current - Average Rectified (Io) (per Diode)10AVoltage - Forward (Vf) (Max) @ If1.15V @ 10ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)45nsCurrent - Reverse Leakage @ Vr100μA @ 200VOperating Temperature - Junction-65°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If1.15V @ 10ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)45nsCurrent - Reverse Leakage @ Vr100μA @ 200VOperating Temperature - Junction-65°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220	Voltage - DC Reverse (Vr) (Max)	200V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)45nsCurrent - Reverse Leakage @ Vr100μA @ 200VOperating Temperature - Junction-65°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220	Current - Average Rectified (Io) (per Diode)	10A
Reverse Recovery Time (trr)45nsCurrent - Reverse Leakage @ Vr100μA @ 200VOperating Temperature - Junction-65°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220	Voltage - Forward (Vf) (Max) @ If	1.15V @ 10A
Current - Reverse Leakage @ Vr100µA @ 200VOperating Temperature - Junction-65°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Operating Temperature - Junction-65°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220	Reverse Recovery Time (trr)	45ns
Mounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220	Current - Reverse Leakage @ Vr	100µA @ 200V
Package / CaseTO-220-3Supplier Device PackageTO-220	Operating Temperature - Junction	-65°C ~ 150°C
Supplier Device Package TO-220	Mounting Type	Through Hole
	Package / Case	TO-220-3
Report errors?	Supplier Device Package	TO-220
		Report errors?

FFP20UP20DNTU Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

FFP20UP20DNTU Payment Methods



FFP20UP20DNTU Shipping Methods



If you have any question about FFP20UP20DNTU, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com