

### **FG560 Information**



Part Number FG560 Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CRTRDGE 560A 550VAC/400VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **FG560 Specifications**

Manufacturer Part NumberFG560ManufacturerEatonCategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesFGFuse TypeCartridgeCurrent Rating560AVoltage Rating - AC550VVoltage Rating - DC400VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.913" Dia x 3.051" L (74.00mm x 77.50mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesFGFuse TypeCartridgeCurrent Rating560AVoltage Rating - AC550VVoltage Rating - DC400VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.913" Dia x 3.051" L (74.00mm x 77.50mm)	Manufacturer Part Number	FG560
PackageElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesFGFuse TypeCartridgeCurrent Rating560AVoltage Rating - AC550VVoltage Rating - DC400VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.913" Dia x 3.051" L (74.00mm x 77.50mm)	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesFGFuse TypeCartridgeCurrent Rating560AVoltage Rating - AC550VVoltage Rating - DC400VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.913" Dia x 3.051" L (74.00mm x 77.50mm)	Category	Circuit Protection
SeriesFGFuse TypeCartridgeCurrent Rating560AVoltage Rating - AC550VVoltage Rating - DC400VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.913" Dia x 3.051" L (74.00mm x 77.50mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating560AVoltage Rating - AC550VVoltage Rating - DC400VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.913" Dia x 3.051" L (74.00mm x 77.50mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating  Voltage Rating - AC  550V  Voltage Rating - DC  400V  Response Time  - Applications  Electrical, Industrial  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Size / Dimension  560A	Series	FG
Voltage Rating - AC  Voltage Rating - DC  400V  Response Time  - Applications  Electrical, Industrial  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Size / Dimension  550V  400V  400V  400V  Approvals  - Cless  - Blectrical, Industrial  - Blectrical, Industrial  - Cless  - Class  Cylindrical, Blade Terminal (Bolt)  2.913" Dia x 3.051" L (74.00mm x 77.50mm)	Fuse Type	Cartridge
Voltage Rating - DC  Response Time - Applications Electrical, Industrial  Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  400V  400V  400V  400V  400V  400V  600  Flexions  600  600  600  600  600  600  600  6	Current Rating	560A
Response Time - Applications Electrical, Industrial  Features - Class	Voltage Rating - AC	550V
Applications Electrical, Industrial  Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.913" Dia x 3.051" L (74.00mm x 77.50mm)	Voltage Rating - DC	400V
Features - Class - Class - Component of the Component of	Response Time	-
Class - Approvals - Class - Coperating Temperature - Streaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.913" Dia x 3.051" L (74.00mm x 77.50mm)	Applications	Electrical, Industrial
Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Bolt Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  2.913" Dia x 3.051" L (74.00mm x 77.50mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  80kA  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  2.913" Dia x 3.051" L (74.00mm x 77.50mm)	Class	-
Breaking Capacity @ Rated Voltage 80kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 2.913" Dia x 3.051" L (74.00mm x 77.50mm)	Approvals	-
Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  2.913" Dia x 3.051" L (74.00mm x 77.50mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.913" Dia x 3.051" L (74.00mm x 77.50mm)	Breaking Capacity @ Rated Voltage	80kA
Size / Dimension 2.913" Dia x 3.051" L (74.00mm x 77.50mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	2.913" Dia x 3.051" L (74.00mm x 77.50mm)
		Report errors?

#### **FG560 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **FG560 Payment Methods**



















### **FG560 Shipping Methods**













If you have any question about FG560, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com