

# FGG.1K.308.CYCK85Z

#### FGG.1K.308.CYCK85Z Information

| Heisener.com       | Part Number<br>Manufacturer<br>Category<br>Description<br>Package | FGG.1K.308.CYCK85Z<br>LEMO<br>Connectors, Interconnects<br>Circular Connectors<br>PLUG INLINE 8PIN CRIMP<br>-<br>For the pricing/inventory/lead time, please contact |                 |
|--------------------|---|--|-----------------|
| For Reference Only |   | us<br>Website: https://www.heisener.com<br>E-mail: salesdept@heisener.com  | Request a Quote |

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## FGG.1K.308.CYCK85Z Specifications

| AnufacturerLEMOConnectors, InterconnectsCircular ConnectorsPackage-Package-SeriesIKConnector TypePlug, Male PinsShell Size - Insert308Shell Size, MIL-Adunting TypeFree Hanging (In-Line)ParentationGirupParentationGParentationPoinsPattersParentationGParentationGParentationPoinsPattersParentationPoinsPattersParentationPoinsPattersParentationGParentationPoinsPattersParentationGoldParentationGoldParentationGoldParentationGoldParentationSackhell, ShieldedParentationSackhell, ShieldedParentationSack  |                          |   |
|---|--------------------------|---|
| CategoryConnectors, InterconnectsCategoryCircular ConnectorsPackage-SeriesIKConnector TypePlug, Male PinsConnector Type8Shell Size - Insert308Shell Size, MIL-Mounting TypeFree Hanging (In-Line)CerminationCrimpFastening TypePush-Pull, Detent LockOrientationGShell Material, FinishBrass, Chrome PlatedShell Material, FinishGoldContact FinishGoldContact FinishSackshell, ShieldedVoltage - Rated-Current RatingShell ShieldedStatening TypeShell ShieldedContact FinishSackshell, ShieldedCurrent RatingShell ShieldedCurrent RatingShell ShieldedCurrent RatingShell ShieldedCurrent RatingShell ShieldedCurrent RatingShell Shell ShieldedCurrent RatingShell Shell ShieldedCurrent RatingShell Shell Sh | Manufacturer Part Number | FGG.1K.308.CYCK85Z                                |
| Circular ConnectorsPackage-SeriesIKConnector TypePlug, Male PinsSometor Type8Shell Size - Insert308Shell Size, MIL-Mounting TypeFree Hanging (In-Line)FerminationCrimpPastening TypePush-Pull, Detent LockPrest ProtectionB66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishGoldContact FinishGoldContact FinishGoldVoltage - Rated-Current Rating5A  | Manufacturer             | LEMO  |
| Package-SeriesIKConector TypePlug, Male PinsConector Type8Number of Positions8Shell Size - Insert308Shell Size, MIL-Mounting TypeFree Hanging (In-Line)FerminationCrimpPastening TypePush-Pull, Detent LockDrientationGngress ProtectionBe668 - Dust Tight, Water Resistant, WaterproofShell Material, FinishGoldContact FinishGoldVoltage - Rated-Current Rating5A   | Category                 | Connectors, Interconnects                         |
| SeriesIKConnector TypePlug, Male PinsNumber of Positions8Shell Size - Insert308Shell Size, MIL-Mounting TypeFree Hanging (In-Line)ForminationCrimpFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionHo6/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating5A   |                          | Circular Connectors                               |
| Connector TypePlug, Male PinsNumber of Positions8Shell Size - Insert308Shell Size, MIL-Mounting TypeFree Hanging (In-Line)FererinationCrimpFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionBrass, Chrome PlatedShell Material, FinishGoldFeaturesBackshell, ShieldedVoltage - RatedSAVoltage - RatedSA  | Package                  | -   |
| Number of Positions8Shell Size - Insert308Shell Size, MIL-Mounting TypeFree Hanging (In-Line)Mounting TypeCrimpFastening TypePush-Pull, Detent LockDrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating5A   | Series                   | 1K  |
| Shell Size - Insert308Shell Size, MIL-Aounting TypeFree Hanging (In-Line)ForminationCrimpFastening TypePush-Pull, Detent LockDrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating5A   | Connector Type           | Plug, Male Pins                                   |
| Shell Size, MIL-Aounting TypeFree Hanging (In-Line)FerminationCrimpFastening TypePush-Pull, Detent LockOrientationGOrientationP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current RatingSh   | Number of Positions      | 8   |
| Mounting TypeFree Hanging (In-Line)FerminationCrimpFastening TypePush-Pull, Detent LockDrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Shell Material, Shielded-  | Shell Size - Insert      | 308   |
| FerminationCrimpFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current RatingSA  | Shell Size, MIL          | -   |
| Fastening TypePush-Pull, Detent LockOrientationGngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current RatingSA   | Mounting Type            | Free Hanging (In-Line)                            |
| DrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current RatingSA  | Termination              | Crimp   |
| ngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current RatingSA   | Fastening Type           | Push-Pull, Detent Lock                            |
| Shell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating5A   | Orientation              | G   |
| Contact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating5A   | Ingress Protection       | IP66/68 - Dust Tight, Water Resistant, Waterproof |
| Features Backshell, Shielded   Voltage - Rated -   Current Rating 5A  | Shell Material, Finish   | Brass, Chrome Plated                              |
| Voltage - Rated-Current Rating5A  | Contact Finish           | Gold  |
| Current Rating 5A   | Features                 | Backshell, Shielded                               |
| -   | Voltage - Rated          | -   |
| Report errors?  | Current Rating           | 5A  |
|   |                          | Report errors?                                    |

#### FGG.1K.308.CYCK85Z Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### FGG.1K.308.CYCK85Z Payment Methods



### FGG.1K.308.CYCK85Z Shipping Methods



If you have any question about FGG.1K.308.CYCK85Z, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com