



#### FGN.3F.322.XLC Information

Heisener.com

Part Number FGN.3F.322.XLC

Manufacturer LEMO

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN INLINE PLUG 22PIN CRIMP

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **FGN.3F.322.XLC Specifications**

Manufacturer Part NumberFGN.3F.322.XLCManufacturerLEMOCategoryConnectors, InterconnectsPackage-Series3FConnector TypePlug, Male PinsNumber of Positions22Shell Size - Insert322Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypePush-Pull, Detent LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating5.5AReport errors?		
CategoryConnectors, InterconnectsPackage-Series3FConnector TypePlug, Male PinsNumber of Positions22Shell Size - Insert322Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypePush-Pull, Detent LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating5.5A	Manufacturer Part Number	FGN.3F.322.XLC
Circular Connectors  Package - Series 3F Connector Type Plug, Male Pins Number of Positions 22 Shell Size - Insert 322 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Crimp Fastening Type Push-Pull, Detent Lock Orientation N (Normal) Ingress Protection NP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating  5.5A	Manufacturer	LEMO
Package - Series 3F Connector Type Plug, Male Pins Number of Positions 22 Shell Size - Insert 322 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Push-Pull, Detent Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 5.5A	Category	Connectors, Interconnects
Series3FConnector TypePlug, Male PinsNumber of Positions22Shell Size - Insert322Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypePush-Pull, Detent LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating5.5A		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions22Shell Size - Insert322Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypePush-Pull, Detent LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating5.5A	Package	-
Number of Positions22Shell Size - Insert322Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypePush-Pull, Detent LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating5.5A	Series	3F
Shell Size - Insert322Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypePush-Pull, Detent LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating5.5A	Connector Type	Plug, Male Pins
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Push-Pull, Detent Lock Orientation N (Normal)  Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Gold  Features Shielded  Voltage - Rated Current Rating 5.5A	Number of Positions	22
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypePush-Pull, Detent LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating5.5A	Shell Size - Insert	322
Termination Crimp Fastening Type Push-Pull, Detent Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated	Shell Size, MIL	-
Fastening Type Push-Pull, Detent Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 5.5A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Gold Features Shielded  Voltage - Rated - Current Rating 5.5A	Termination	Crimp
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 5.5A	Fastening Type	Push-Pull, Detent Lock
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating Shell Material, Finish Gold Contact Finish Gold Shielded Shielded	Orientation	N (Normal)
Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 5.5A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Shielded  Voltage - Rated - Current Rating 5.5A	Shell Material, Finish	Aluminum Alloy, Nickel Plated
Voltage - Rated - Current Rating 5.5A	Contact Finish	Gold
Current Rating 5.5A	Features	Shielded
	Voltage - Rated	-
Report errors?	Current Rating	5.5A
		Report errors?

#### FGN.3F.322.XLC Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# FGN.3F.322.XLC Payment Methods





















### FGN.3F.322.XLC Shipping Methods













If you have any question about FGN.3F.322.XLC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com