

**FI-SE30P-HFE-E3000 Information**


For Reference Only

**Part Number** [FI-SE30P-HFE-E3000](#)  
**Manufacturer** JAE Electronics  
**Category** Connectors, Interconnects  
[Rectangular Connectors - Headers, Male Pins](#)  
**Description** CONN RCPT 1.25MM 30POS SMD R/A  
**Package** -  
 For the pricing/inventory/lead time, please contact us  
 Website: <https://www.heisener.com>  
 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)


[Request a Quote](#)
**Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.


**FI-SE30P-HFE-E3000 Specifications**

|                            |  |
|----------------------------|--|
| Manufacturer Part Number   | <a href="#">FI-SE30P-HFE-E3000</a>   |
| Manufacturer               | JAE Electronics  |
| Category                   | Connectors, Interconnects<br><a href="#">Rectangular Connectors - Headers, Male Pins</a> |
| Package                    | -  |
| Series                     | FI   |
| Connector Type             | Receptacle   |
| Contact Type               | Male Pin   |
| Pitch - Mating             | 0.049" (1.25mm)  |
| Style                      | Board to Cable/Wire  |
| Shrouding                  | Shrouded - 4 Wall  |
| Number of Positions        | 30   |
| Number of Positions Loaded | All  |
| Number of Rows             | 1  |
| Row Spacing - Mating       | -  |
| Mounting Type              | Surface Mount, Right Angle   |
| Termination                | Solder   |
| Fastening Type             | Friction Lock  |
| Contact Length - Mating    | -  |
| Contact Length - Post      | -  |
| Overall Contact Length     | -  |
| Insulation Height          | 0.083" (2.10mm)  |
| Contact Shape              | Square   |
| Contact Finish - Mating    | Gold   |

|                                   |  |
|-----------------------------------|--|
| Contact Finish Thickness - Mating | -  |
| Contact Finish - Post             | Tin or Tin-Alloy                           |
| Contact Material                  | Copper Alloy                               |
| Insulation Material               | Liquid Crystal Polymer (LCP), Glass Filled |
| Features                          | Shielded, Solder Retention                 |
| Operating Temperature             | -40°C ~ 80°C                               |
| Ingress Protection                | -  |
| Material Flammability Rating      | UL94 V-0                                   |
| Insulation Color                  | Beige                                      |
| <a href="#">Report errors?</a>    |  |

## FI-SE30P-HFE-E3000 Guarantees



### Quality Guarantees

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## FI-SE30P-HFE-E3000 Payment Methods



## FI-SE30P-HFE-E3000 Shipping Methods



If you have any question about FI-SE30P-HFE-E3000, please do not hesitate to contact us!

Website: <https://www.heisener.com>

E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)