

**FI-XB30SSRL-HF16 Information**


For Reference Only

**Part Number** [FI-XB30SSRL-HF16](#)  
**Manufacturer** JAE Electronics  
**Category** Connectors, Interconnects  
[Rectangular Connectors - Headers, Receptacles, Female Sockets](#)  
**Description** CONN RCPT 30POS 1.0MM R/A SMD  
**Package** -  
 For the pricing/inventory/lead time, please contact us  
 Website: <https://www.heisener.com>  
 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)



[Request a Quote](#)

**Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.


**FI-XB30SSRL-HF16 Specifications**

|                                   |                                                                                                            |
|-----------------------------------|------------------------------------------------------------------------------------------------------------|
| Manufacturer Part Number          | <a href="#">FI-XB30SSRL-HF16</a>                                                                           |
| Manufacturer                      | JAE Electronics                                                                                            |
| Category                          | Connectors, Interconnects<br><a href="#">Rectangular Connectors - Headers, Receptacles, Female Sockets</a> |
| Package                           | -                                                                                                          |
| Series                            | FI-X                                                                                                       |
| Connector Type                    | Receptacle                                                                                                 |
| Contact Type                      | Non-Gendered                                                                                               |
| Style                             | Board to Cable/Wire                                                                                        |
| Number of Positions               | 30                                                                                                         |
| Number of Positions Loaded        | All                                                                                                        |
| Pitch - Mating                    | 0.039" (1.00mm)                                                                                            |
| Number of Rows                    | 1                                                                                                          |
| Row Spacing - Mating              | -                                                                                                          |
| Mounting Type                     | Board Cutout, Bottom Mount, Surface Mount, Right Angle, Reverse Mount                                      |
| Termination                       | Solder                                                                                                     |
| Fastening Type                    | Friction Lock                                                                                              |
| Contact Finish - Mating           | Gold                                                                                                       |
| Contact Finish Thickness - Mating | 3.9µin (0.10µm)                                                                                            |
| Insulation Color                  | Black                                                                                                      |
| Insulation Height                 | -                                                                                                          |
| Contact Length - Post             | -                                                                                                          |
| Operating Temperature             | -40°C ~ 80°C                                                                                               |
| Material Flammability Rating      | UL94 V-0                                                                                                   |

|                        |                                            |
|------------------------|--------------------------------------------|
| Contact Finish - Post  | Tin                                        |
| Mated Stacking Heights | -                                          |
| Ingress Protection     | -                                          |
| Features               | Grounding Pins, Shielded, Solder Retention |

[Report errors?](#)

## FI-XB30SSRL-HF16 Guarantees



### Quality Guarantees

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## FI-XB30SSRL-HF16 Payment Methods



## FI-XB30SSRL-HF16 Shipping Methods



If you have any question about FI-XB30SSRL-HF16, please do not hesitate to contact us!

Website: <https://www.heisener.com>

E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)