

FLE-141-01-G-DV-A-P

FLE-141-01-G-DV-A-P Information

age	-	自然要求
	For the pricing/inventory/lead time, please contact us	Request a Quote
	-	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



FLE-141-01-G-DV-A-P Specifications

Manufacturer Part NumberFLE-141-01-G-DV-A-PManufacturerSamtee Inc.CategoryConnectors, InterconnectsPackage-Package-SeriesFLEContact TypeReceptacles, Receptacles, Female SocketsContact TypeReceptacleContact TypeBoard to Board or CableNumber of Positions82Number of Positions LoadedAllPitch - Mating0.050" (1.27mm)Number of Rows2Remain SocketSurface MountFrancisco Mounting TypeSurface MountYatea MountSolderFastening TypeOids" (1.27mm)Contact Finish - MatingGoldContact Finish - MatingGoldContact Finish - MatingJoin (0.25µm)Contact Finish - MatingGoldContact Finish - MatingI.012" (4.37mm)Contact Finish Thickness - MatingJoin (0.25µm)Insulation ColorBackContact Lengt - Post-Contact Lengt - Post-Material Flammability Rating-		
Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series FLE Connector Type Receptacle Contact Type Receptacle Contact Type Board to Board or Cable Number of Positions 82 Number of Positions Loaded All Number of Rows 2 Row Spacing - Mating 0.050° (1.27mm) Mounting Type Solder Yernination Solder Fastening Type Solder Contact Finish - Mating Gold Contact Finish Thickness - Mating Jupin (0.25µm) Solder Solder Finisultion Color Black Insulation Color Black Insulation Height 0.172° (4.37mm) Contact Length - Post -	Manufacturer Part Number	FLE-141-01-G-DV-A-P
Package-SeriesFLEConnector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions82Number of Positions LoadedAllPitch - Mating0.050" (1.27mm)Number of Rows2Row Spacing - MatingSolderTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJujin (0.25µm)Soltact Finish Thickness - MatingJujin (0.25µm)Contact Finish Thickness - MatingJujin (0.25µm)Insulation Height0.172" (4.37mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Manufacturer	Samtec Inc.
Package-SeriesFLEConnector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions82Number of Positions LoadedAllPitch - Mating0.050° (1.27mm)Number of Rows2Row Spacing - Mating0.050° (1.27mm)Mounting Type0.050° (1.27mm)Yenning TypeSolderFerminationSolderFortaur TypeSolderContact Finish - MatingGoldContact Finish Thickness - MatingIlpin (0.25µm)Insulation ColorBlackInsulation Height0.172° (4.37mm)Contact Length - Post-Operating Temperature55°C ~ 125°C	Category	Connectors, Interconnects
SeriesFLEConnector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions82Number of Positions LoadedAllPitch - Mating0.50° (1.27mm)Number of Rows2Row Spacing - Mating0.50° (1.27mm)Mounting TypeSurface MountTerminationSolderContact Finish - MatingGoldContact Finish - MatingGoldSundator ColorJupin (0.25µm)Insulation ColorBlackInsulation Height0.172" (4.37mm)Contact Fungh-Post-Strace Nations-Sundator Height-Solar Contact Fungh-Post-Strace NationsSickStration ColorSickStration Height-Stration Height-Stration FungerAture-Stration FungerAture-Stration Height-Stration Stration-Stration Stration-Stration Height-Stration Stration-Stration Height-Stration Stration-Stration Stration-Stration Height-Stration Stration-Stration Stration Stration-Stration Stration Stration-Stration Stration Stration Stration-Stration Stration Stra		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions82Number of Positions LoadedAllPitch - Mating0.50° (1.27mm)Number of Rows2Row Spacing - Mating0.50° (1.27mm)Mounting TypeSurface MountForminationSolderContact Finish - MatingSolderContact Finish - MatingGoldInsulation ColorBlackInsulation Right0.17° (4.37mm)Contact Length - Post-Store - L2S°C-S°C ~ 12S°C	Package	-
Contact TypeFemale SocketStyleBoard to Board or CableNumber of Positions82Number of Positions LoadedAllPitch - Mating0.050" (1.27mm)Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - Mating0.04Insulation ColorBlackInsulation Height0.172" (4.37mm)Contact Length - Post-Sperating Temperature-55°C ~ 125°C	Series	FLE
StyleBoard to Board or CableNumber of Positions82Number of Positions LoadedAllPitch - Mating0.050" (1.27mm)Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.172" (4.37mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Connector Type	Receptacle
Number of Positions 82 Number of Positions Loaded All Pitch - Mating 0.050" (1.27mm) Number of Rows 2 Row Spacing - Mating 0.050" (1.27mm) Mounting Type 0.050" (1.27mm) Fermination 0.050" (1.27mm) Termination Solder Fastening Type Solder Contact Finish - Mating Gold Contact Finish Thickness - Mating 10µin (0.25µm) Insulation Color Black Insulation Height 0.172" (4.37mm) Contact Length - Post - Operating Temperature -55°C ~ 125°C	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.050" (1.27mm)Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingIlpuin (0.25µm)Insulation ColorBlackInsulation Height0.172" (4.37mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Style	Board to Board or Cable
Pitch - Mating0.050" (1.27mm)Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSurface MountFastening TypePosh-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation Color0.172" (4.37mm)Contact Length - Post-55°C ~ 125°C	Number of Positions	82
Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.172" (4.37mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Number of Positions Loaded	All
Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingIupin (0.25µm)Insulation ColorBlackInsulation Height0.172" (4.37mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Pitch - Mating	0.050" (1.27mm)
Mounting TypeSurface MountForminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.172" (4.37mm)Contact Length - Post-Operating Temperature55°C ~ 125°C	Number of Rows	2
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.172" (4.37mm)Contact Length - Post-Operating Temperature55°C ~ 125°C	Row Spacing - Mating	0.050" (1.27mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.172" (4.37mm)Contact Length - Post-Operating Temperature55°C ~ 125°C	Mounting Type	Surface Mount
Contact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.172" (4.37mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Termination	Solder
Contact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.172" (4.37mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.172" (4.37mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold
Insulation Height0.172" (4.37mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Contact Finish Thickness - Mating	10µin (0.25µm)
Contact Length - Post-Operating Temperature-55°C ~ 125°C	Insulation Color	Black
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Insulation Height	0.172" (4.37mm)
	Contact Length - Post	-
Material Flammability Rating -	Operating Temperature	-55°C ~ 125°C
	Material Flammability Rating	-

Contact Finish - Post	Gold
Mated Stacking Heights	-
Ingress Protection	-
Features	Board Guide, Pick and Place

Report errors?

FLE-141-01-G-DV-A-P Guarantees



Quality Guarantees


We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

FLE-141-01-G-DV-A-P Payment Methods



If you have any question about FLE-141-01-G-DV-A-P, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com