



FLNR.800T Information

(A) Heisener.com

Part NumberFLNR.800TManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 800MA 250VAC/125VDC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FLNR.800T Specifications

Manufacturer Part NumberFLNR.800TManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? FLNRFuse TypeCartridgeCurrent Rating800mAVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)Report errors?		
Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD? FLNR Fuse Type Cartridge Current Rating 800mA Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Circuit Protection Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension Circuit Protection Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension	Manufacturer Part Number	FLNR.800T
Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD? FLNR Fuse Type Cartridge Current Rating 800mA Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD? FLNRFuse TypeCartridgeCurrent Rating800mAVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Category	Circuit Protection
SeriesPOWR-GARD? FLNRFuse TypeCartridgeCurrent Rating800mAVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating800mAVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Package	Cartridge, Non-Standard
Current Rating 800mA Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Series	POWR-GARD? FLNR
Voltage Rating - AC Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 250V 250V 260V 2	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 125V 125V	Current Rating	800mA
Response Time Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Slow Slow Slow Slow Slow Electrical, Industrial - CK, CSA, QPL, UL - CE,	Voltage Rating - AC	250V
Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Voltage Rating - DC	125V
Features - Class RK5 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Response Time	Slow
Class RK5 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Applications	Electrical, Industrial
Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Class	RK5
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Approvals	CE, CSA, QPL, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.563" Dia x 2.000" L (14.30mm x 50.80mm)
		Report errors?

FLNR.800T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FLNR.800T Payment Methods



















FLNR.800T Shipping Methods













If you have any question about FLNR.800T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com