



### **FLNR050.T Information**

Manufa Categor Heisener.com

Part NumberFLNR050.TManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 50A 250VAC/125VDC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **FLNR050.T Specifications**

Manufacturer Part NumberFLNR050.TManufacturerLittelfuse Inc.CategoryCircuit ProtectionBeckageCartridge, Non-StandardSeriesPOWR-GARD? FLNRFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.000" L (20.60mm x 76.20mm)Report errors?		
Category  Circuit Protection  Electrical, Specialty Fuses  Package  Cartridge, Non-Standard  Series  POWR-GARD? FLNR  Fuse Type  Cartridge  Current Rating  50A  Voltage Rating - AC  Voltage Rating - DC  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  RK5  Approvals  CE, CSA, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  Cartridge, Non-Standard  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  Cartridge, Non-Standard  Size / Dimension  Cartridge, Non-Standard  Size / Dimension	Manufacturer Part Number	FLNR050.T
Electrical, Specialty Fuses  Package Cartridge, Non-Standard  Series POWR-GARD? FLNR  Fuse Type Cartridge  Current Rating 50A  Voltage Rating - AC 250V  Voltage Rating - DC 125V  Response Time Slow  Applications Electrical, Industrial  Features - Class RK5  Approvals CE, CSA, QPL, UL  Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD? FLNRFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Category	Circuit Protection
SeriesPOWR-GARD? FLNRFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.000" L (20.60mm x 76.20mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating50AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Sinner Sinne	Series	POWR-GARD? FLNR
Voltage Rating - AC  Voltage Rating - DC  125V  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  RK5  Approvals  CE, CSA, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  250V  250V  260V  2	Fuse Type	Cartridge
Voltage Rating - DC  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  RK5  Approvals  CE, CSA, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  125V  125V	Current Rating	50A
Response Time  Applications  Electrical, Industrial  Features  - Class  RK5  Approvals  CE, CSA, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  Slow  Slow  Slow  Slow  Slow  Electrical, Industrial  -  CK, CSA, QPL, UL  - CE,	Voltage Rating - AC	250V
Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Voltage Rating - DC	125V
Features - Class RK5  Approvals CE, CSA, QPL, UL  Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Response Time	Slow
Class RK5 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Applications	Electrical, Industrial
Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  200kA AC, 20kA DC  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Class	RK5
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Approvals	CE, CSA, QPL, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.811" Dia x 3.000" L (20.60mm x 76.20mm)
		Report errors?

### **FLNR050.T Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **FLNR050.T Payment Methods**



















## **FLNR050.T Shipping Methods**













If you have any question about FLNR050.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com