



### **FLNR080.V Information**

(A) Heisener.com

Part NumberFLNR080.VManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 80A 250VAC/125VDC

Package Cylindrical, Blade Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **FLNR080.V Specifications**

| Manufacturer Part NumberFLNR080.VManufacturerLittelfuse Inc.CategoryCircuit ProtectionPackageCylindrical, Specialty FusesSeriesPOWR-GARD? FLNRFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.063" Dia x 5.874" L (27.00mm x 149.20mm)Report errors?  |                                   |  |
|--|-----------------------------------|--|
| CategoryCircuit ProtectionPackageCylindrical, Specialty FusesSeriesPOWR-GARD? FLNRFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.063" Dia x 5.874" L (27.00mm x 149.20mm)  | Manufacturer Part Number          | FLNR080.V                                  |
| Beaking Capacity @ Rated Voltage  Electrical, Specialty Fuses  Cylindrical, Blade Terminals  Cylindrical, Blade Terminals  POWR-GARD? FLNR  Cartridge  Current Rating  80A  Voltage Rating - AC  250V  Voltage Rating - DC  125V  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  RK5  Approvals  CE, CSA, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cylindrical, Blade Terminals  Size / Dimension  Electrical, Blade Terminals  Size / Dimension   | Manufacturer                      | Littelfuse Inc.                            |
| PackageCylindrical, Blade TerminalsSeriesPOWR-GARD? FLNRFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.063" Dia x 5.874" L (27.00mm x 149.20mm)  | Category                          | Circuit Protection                         |
| SeriesPOWR-GARD? FLNRFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.063" Dia x 5.874" L (27.00mm x 149.20mm)   |                                   | Electrical, Specialty Fuses                |
| Fuse Type Current Rating 80A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  Cartridge Rated Solw ROA  250V  Light V  Electrical Ridustrial CEC, CSA, QPL  CEC, CSA, QPL  CEC, CSA, QPL, UL  COPITATION COMMENT | Package                           | Cylindrical, Blade Terminals               |
| Current Rating  Voltage Rating - AC  250V  Voltage Rating - DC  125V  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  RK5  Approvals  CE, CSA, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  80A  80A  80A  80A  80A  250V  250V  250V  125V  Response Time  Slow  Cley  CSV  CE, CSA  COL  COL  COL  COL  COL  COL  COL  CO  | Series                            | POWR-GARD? FLNR                            |
| Voltage Rating - AC  Voltage Rating - DC  125V  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  RK5  Approvals  CE, CSA, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  250V  250V  250V  260V  2 | Fuse Type                         | Cartridge                                  |
| Voltage Rating - DC  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  RK5  Approvals  CE, CSA, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  1.063" Dia x 5.874" L (27.00mm x 149.20mm)   | Current Rating                    | 80A  |
| Response Time  Applications  Electrical, Industrial  Features  - Class  RK5  Approvals  CE, CSA, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cylindrical, Blade Terminals  1.063" Dia x 5.874" L (27.00mm x 149.20mm)  | Voltage Rating - AC               | 250V                                       |
| Applications Electrical, Industrial  Features - Class RK5  Approvals CE, CSA, QPL, UL  Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cylindrical, Blade Terminals  Size / Dimension 1.063" Dia x 5.874" L (27.00mm x 149.20mm)   | Voltage Rating - DC               | 125V                                       |
| Features - Class RK5  Approvals CE, CSA, QPL, UL  Operating Temperature - Package / Case Cylindrical, Blade Terminals  Size / Dimension - 1.063" Dia x 5.874" L (27.00mm x 149.20mm)   | Response Time                     | Slow                                       |
| Class RK5 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.063" Dia x 5.874" L (27.00mm x 149.20mm)  | Applications                      | Electrical, Industrial                     |
| Approvals  CE, CSA, QPL, UL  Operating Temperature  - Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cylindrical, Blade Terminals  Size / Dimension  CE, CSA, QPL, UL  CHARACTOR OF COMMON OF | Features                          | -  |
| Operating Temperature  Breaking Capacity @ Rated Voltage  200kA AC, 20kA DC  Mounting Type  Holder  Package / Case  Cylindrical, Blade Terminals  Size / Dimension  1.063" Dia x 5.874" L (27.00mm x 149.20mm)   | Class                             | RK5  |
| Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cylindrical, Blade Terminals  Size / Dimension 1.063" Dia x 5.874" L (27.00mm x 149.20mm)  | Approvals                         | CE, CSA, QPL, UL                           |
| Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.063" Dia x 5.874" L (27.00mm x 149.20mm)   | Operating Temperature             | -  |
| Package / Case Cylindrical, Blade Terminals Size / Dimension 1.063" Dia x 5.874" L (27.00mm x 149.20mm)  | Breaking Capacity @ Rated Voltage | 200kA AC, 20kA DC                          |
| Size / Dimension 1.063" Dia x 5.874" L (27.00mm x 149.20mm)  | Mounting Type                     | Holder                                     |
|  | Package / Case                    | Cylindrical, Blade Terminals               |
| Report errors?   | Size / Dimension                  | 1.063" Dia x 5.874" L (27.00mm x 149.20mm) |
|  |                                   | Report errors?                             |

#### **FLNR080.V Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **FLNR080.V Payment Methods**



















### **FLNR080.V Shipping Methods**













If you have any question about FLNR080.V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com