



FLNR090.VXID Information

Heisener.com

Part NumberFLNR090.VXIDManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 90A 250VAC/125VDC

Package Cylindrical, Blade Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FLNR090.VXID Specifications

Manufacturer Part NumberFLNR090.VXIDManufacturerLittelfuse Inc.CategoryCircuit ProtectionPackageCylindrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesPOWR-GARD? FLNR_IDFuse TypeCartridgeCurrent Rating90AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.063" Dia x 5.874" L (27.00mm x 149.20mm)Report errors?		
CategoryCircuit ProtectionBectrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesPOWR-GARD? FLNR_IDFuse TypeCartridgeCurrent Rating90AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.063" Dia x 5.874" L (27.00mm x 149.20mm)	Manufacturer Part Number	FLNR090.VXID
Beckrical, Specialty Fuses Cylindrical, Blade Terminals Series POWR-GARD? FLNR_ID Fuse Type Cartridge Current Rating 90A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension Electrical, Industrial 1.063" Dia x 5.874" L (27.00mm x 149.20mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade TerminalsSeriesPOWR-GARD? FLNR_IDFuse TypeCartridgeCurrent Rating90AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.063" Dia x 5.874" L (27.00mm x 149.20mm)	Category	Circuit Protection
SeriesPOWR-GARD? FLNR_IDFuse TypeCartridgeCurrent Rating90AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.063" Dia x 5.874" L (27.00mm x 149.20mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 90A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cartridge Package Cartridge Package Cartridge Package Cartridge Package Size / Dimension Cartridge Package Cartridge Package Cartridge Package Cartridge Package Size / Dimension Lactridge Package Cartridge Package Cartridge Package Cartridge Package Size / Dimension Cartridge Package Cartridge Package Cartridge Package Cartridge Package Pac	Package	Cylindrical, Blade Terminals
Current Rating 90A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.063" Dia x 5.874" L (27.00mm x 149.20mm)	Series	POWR-GARD? FLNR_ID
Voltage Rating - AC Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 250V 250V 250V 260V 260	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features Indicating RK5 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 1.063" Dia x 5.874" L (27.00mm x 149.20mm)	Current Rating	90A
Response Time Applications Electrical, Industrial Features Indicating RK5 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals 1.063" Dia x 5.874" L (27.00mm x 149.20mm)	Voltage Rating - AC	250V
Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.063" Dia x 5.874" L (27.00mm x 149.20mm)	Voltage Rating - DC	125V
Features Indicating Class RK5 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.063" Dia x 5.874" L (27.00mm x 149.20mm)	Response Time	Slow
Class RK5 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.063" Dia x 5.874" L (27.00mm x 149.20mm)	Applications	Electrical, Industrial
Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension CE, CSA, QPL, UL CHARACTOR OF COMMON OF	Features	Indicating
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.063" Dia x 5.874" L (27.00mm x 149.20mm)	Class	RK5
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.063" Dia x 5.874" L (27.00mm x 149.20mm)	Approvals	CE, CSA, QPL, UL
Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.063" Dia x 5.874" L (27.00mm x 149.20mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminals Size / Dimension 1.063" Dia x 5.874" L (27.00mm x 149.20mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 1.063" Dia x 5.874" L (27.00mm x 149.20mm)	Mounting Type	Holder
	Package / Case	Cylindrical, Blade Terminals
Report errors?	Size / Dimension	1.063" Dia x 5.874" L (27.00mm x 149.20mm)
		Report errors?

FLNR090.VXID Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FLNR090.VXID Payment Methods





















FLNR090.VXID Shipping Methods













If you have any question about FLNR090.VXID, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com