



FLSR002.T Information

Manufacturer Littelfuse Inc. Category Heisener.com

Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 2A 600VAC/300VDC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

Part Number FLSR002.T

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FLSR002.T Specifications

Manufacturer Part NumberFLSR002.TManufacturerLittelfuse Inc.CategoryCircuit ProtectionPackageCartridge, Non-StandardSeriesPOWR-GARD? FLSRFuse TypeCartridgeCurrent Rating2AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 5.000" L (20.60mm x 127.00mm)Report errors?		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? FLSRFuse TypeCartridgeCurrent Rating2AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Manufacturer Part Number	FLSR002.T
PackageElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? FLSRFuse TypeCartridgeCurrent Rating2AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD? FLSRFuse TypeCartridgeCurrent Rating2AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Category	Circuit Protection
SeriesPOWR-GARD? FLSRFuse TypeCartridgeCurrent Rating2AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 5.000" L (20.60mm x 127.00mm)		Electrical, Specialty Fuses
Fuse Type Current Rating Current Rating 2A Voltage Rating - AC Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cannot Converted Survey Cartridge, Non-Standard Size / Dimension Cannot Cartridge, Non-Standard Size / Dimension Cannot Converted Survey Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Cartridge, Non-Stand	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 2A 600V 600V 600V 600V 600V 600V 600V 600	Series	POWR-GARD? FLSR
Voltage Rating - AC Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 6	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 300V 300V 300V 300V 300V Approvals CE, CSA, QPL, UL - CE, CSA, CE, CSA,	Current Rating	2A
Response Time Applications Electrical, Industrial Features - Class RK5 Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Slow Slow Slow Slow Slow Slow Slow Slow Electrical, Industrial - CE, CSA, QPL, UL CE, CSA, QPL, UL - CE, CSA, QPL - CE, CS	Voltage Rating - AC	600V
Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Voltage Rating - DC	300V
Features - Class RK5 Approvals CE, CSA, QPL, UL Operating Temperature - Streaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Response Time	Slow
Class RK5 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Applications	Electrical, Industrial
Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Class	RK5
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Approvals	CE, CSA, QPL, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.811" Dia x 5.000" L (20.60mm x 127.00mm)
_		Report errors?

FLSR002.T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FLSR002.T Payment Methods





















FLSR002.T Shipping Methods













If you have any question about FLSR002.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com