



## **FLSR005.TXID Information**

Heisener.com

Part Number FLSR005.TXID
Manufacturer Littelfuse Inc.
Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 5A 600VAC/300VDC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **FLSR005.TXID Specifications**

Manufacturer Part Number  Manufacturer  Littelfuse Inc.  Category  Circuit Protection  Electrical, Specialty Fuses  Package  Cartridge, Non-Standard  Series  POWR-GARD? FLSR_ID  Fuse Type  Cartridge  Current Rating  5A  Voltage Rating - AC  Voltage Rating - DC  Response Time  Applications  Electrical, Industrial  Features  Indicating  Class  RK5  Approvals  CE, CSA, QPL, UL  Operating Temperature  Package / Case  Cartridge, Non-Standard  O.811" Dia x 5.000" L (20.60mm x 127.00mm)		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? FLSR_IDFuse TypeCartridgeCurrent Rating5AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Manufacturer Part Number	FLSR005.TXID
PackageElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? FLSR_IDFuse TypeCartridgeCurrent Rating5AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD? FLSR_IDFuse TypeCartridgeCurrent Rating5AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Category	Circuit Protection
SeriesPOWR-GARD? FLSR_IDFuse TypeCartridgeCurrent Rating5AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 5.000" L (20.60mm x 127.00mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating5AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Signature  5A 600V 600V 600V 600V 600V 600V 600V 600	Series	POWR-GARD? FLSR_ID
Voltage Rating - AC  Voltage Rating - DC  300V  Response Time  Slow  Applications  Electrical, Industrial  Features  Indicating  Class  RK5  Approvals  CE, CSA, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  600V  600	Fuse Type	Cartridge
Voltage Rating - DC  Response Time  Slow  Applications  Electrical, Industrial  Features  Indicating  RK5  Approvals  CE, CSA, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  300V  300V  300V  300V  300V  Approvals  Electrical, Industrial  Indicating  RK5  CE, CSA, QPL, UL  - Catridge, Non-Standard  0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Current Rating	5A
Response Time  Applications  Electrical, Industrial  Features  Indicating  Class  RK5  Approvals  CE, CSA, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  Slow  Sl	Voltage Rating - AC	600V
Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Voltage Rating - DC	300V
Features Indicating Class RK5  Approvals CE, CSA, QPL, UL  Operating Temperature -  Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Response Time	Slow
Class RK5 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Applications	Electrical, Industrial
Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Features	Indicating
Operating Temperature  Breaking Capacity @ Rated Voltage  200kA AC, 20kA DC  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Class	RK5
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Approvals	CE, CSA, QPL, UL
Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.811" Dia x 5.000" L (20.60mm x 127.00mm)
L. Control of the con		Report errors?

#### **FLSR005.TXID Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **FLSR005.TXID Payment Methods**



















### **FLSR005.TXID Shipping Methods**













If you have any question about FLSR005.TXID, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com