

FMB05DYFN

FMB05DYFN Information

Heisener.com	 FMB05DYFN Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 10POS 0.050 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



FMB05DYFN Specifications

ManufacturerSullins Connector SolutionsCardectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Package-Stries-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row5Number of Positions0.062" (1.57mm)Number of Rows2Pich0.050" (1.27mm)Features-Mounting TypeSulface MountYounder StrinshSulface MountContact MaterialSolderContact Finish ThicknessGoldContact TypeGuil (0.76µm)Contact TypeGuil (0.76µm)Contact TypeSulface MountContact TypeSulface MountContact TypeSulface MountContact Finish ThicknessSulface MountContact Finish ThicknessSulface MountContact TypeGuil (0.76µm)Contact TypeSulface MountContact TypeSulface Mount </th <th>-</th> <th></th>	-	
CategoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row5Number of Positions/Bay/Row0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSuface MountContact MaterialSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverContact TypeBlackFlange Feature-Coperating Temperature-Operating Temperature-Contact SectorSolderContact SectorSolderContact TypeCantileverContact TypeCantileverContact TypeCantileverColorBlackFlange Feature-Contact SectorSolderContact SectorSolder <td>Manufacturer Part Number</td> <td>FMB05DYFN</td>	Manufacturer Part Number	FMB05DYFN
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row5Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeCantileverContact TypeCantileverContact TypeSurfaceContact TypeCantileverContact TypeSolderContact TypeSolderContact TypeCantileverContact TypeCantileverColorBlackFinage Feature-Operating Temperature-5°C ~ 200°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row5Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeCantileverContact TypeCantileverColorBlackFlange Feature-Operating Temperature-5°C ~ 200°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row5Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountContact Finish ThicknessSolderContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row5Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountContact MaterialSolderContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact TypeBlackFlange Feature-Operating Temperature65°C ~ 200°C	Package	_
GenderFemaleNumber of Positions/Bay/Row5Number of Positions10Card Thickness0.602° (1.57mm)Number of Rows2Pitch0.50° (1.27mm)Features-Mounting TypeSuface MountContact MaterialSolderContact FinishGoldContact Finish ThicknessGoldContact TypeSupin (0.76µm)Contact Finish ThicknessSupin (0.76µm)Contact Finish ThicknessSupin (0.76µm)Contact TypeGalactFinage Feature-Operating Temperature65°C ~ 200°C	Series	-
Number of Positions/Bay/Row5Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountContact MaterialSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature65°C ~ 20°C	Card Type	Non Specified - Dual Edge
Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountTerminationSolderContact MaterialSpinodalContact Finish ThicknessGoldContact TypeCantileverColorBlackFlange Feature-Operating Temperature-55°C ~ 200°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountTerminationSolderContact MaterialSpinodalContact Finish ThicknessGoldContact TypeCantileverColorBlackFlange Features-Operating Temperature-65°C ~ 200°C	Number of Positions/Bay/Row	5
Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountTerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Number of Positions	10
Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountTerminationSolderContact MaterialSpinodalContact Finish ThicknessGoldContact TypeSupin (0.76µm)ColorBlackFlange Feature-Operating Temperature-55°C ~ 200°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeSurface MountTerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish Thickness3µin (0.76µm)Contact TypeBlackFlange Feature-Operating Temperatures-5°C ~ 200°C	Number of Rows	2
Mounting TypeSurface MountTerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-55°C ~ 200°C	Pitch	0.050" (1.27mm)
TerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Features	-
Contact MaterialSpinodalContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Mounting Type	Surface Mount
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Termination	Solder
Contact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Contact Material	Spinodal
Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Contact Finish	Gold
Color Black Flange Feature - Operating Temperature -65°C ~ 200°C	Contact Finish Thickness	30µin (0.76µm)
Flange Feature-Operating Temperature-65°C ~ 200°C	Contact Type	Cantilever
Operating Temperature $-65^{\circ}\text{C} \sim 200^{\circ}\text{C}$	Color	Black
	Flange Feature	-
Report errors?	Operating Temperature	$-65^{\circ}C \sim 200^{\circ}C$
		Report errors?

FMB05DYFN Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

FMB05DYFN Payment Methods



FMB05DYFN Shipping Methods



If you have any question about FMB05DYFN, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com