

FMB05DYFR

FMB05DYFR Information

Heisener.com	 FMB05DYFR Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 10POS 0.050 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



FMB05DYFR Specifications

ManufacturerSullins Connector SolutionsCardecors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Package-Stries-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row5Number of Positions0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeSulface MountContact FinishSolderContact Finish ThicknessGoldContact TypeGuid (0.76µm)Contact TypeGuid (0.76µm)Contact TypeGuid (0.76µm)Contact TypeGuid (0.76µm)Contact TypeSulface Contact (0.76µm)Contact TypeGuid (0.76µm)<	-	
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row5Number of Positions/Bay/Row0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeSufface MountContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeCantileverContact TypeGaldContact TypeBlackFaquere-ColorBlackFaquere-Operating Temperature-55°C ~ 200°C	Manufacturer Part Number	FMB05DYFR
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row5Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeSurface MountContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeCantileverContact TypeCantileverContact TypeCantileverColorBlackFlange Feature-Operating Temperature-5°C ~ 200°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row5Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeSurface MountContact MaterialSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverContact TypeCantileverColorBlackFlange Feature-Operating Temperature-5°C ~ 200°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row5Number of Positions/Bay/Row10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeSurface MountContact Finish ThicknessSolderContact Finish ThicknessGoldContact TypeSurfaceAcaContact TypeSufareContact TypeSufareContact TypeSufareContact TypeSufareContact TypeSufareContact TypeSufareContact TypeSalekFeature-ColorBlackFeature-Operating Temperature-65°C ~ 200°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row5Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeSurface MountContact MaterialSolderContact FinishGoldContact Finish ThicknessGoldContact TypeCantileverColorBlackFlange Feature-Operating Temperature65°C ~ 200°C	Package	-
GenderFemaleNumber of Positions/Bay/Row5Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeSurface MountContact FinishSolderContact Finish ThicknessGoldContact TypeGuid (0.76µm)Contact TypeSurjace MountContact TypeSurjace MountFange FeatureSolderForge FeatureGoldForge FeatureSolderCortact TypeSolderFange Feature-Operating Temperature-SolderSolderFeature-Contact FinishSolderColorBlackFange Feature-Operating Temperature-Solder <td>Series</td> <td>-</td>	Series	-
Number of Positions/Bay/Row5Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeSulface MountContact MaterialSolderContact FinishGoldContact TypeGujui (0.76µm)Contact TypeSulfaceContact TypeSulfaceContact TypeSulfaceColorBlackFange Feature-Operating Temperature65°C ~ 20°C	Card Type	Non Specified - Dual Edge
Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeSurface MountTerminationSolderContact MaterialGoldContact Finish ThicknessGoldContact TypeCantileverColorBlackFlange Feature-Operating Temperature65°C ~ 20°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeSurface MountTerminationSolderContact MaterialSpinodalContact Finish ThicknessGoldContact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Number of Positions/Bay/Row	5
Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeSurface MountTerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Number of Positions	10
Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeSurface MountTerminationSolderContact MaterialSpinodalContact Finish ThicknessGoldContact TypeSupin (0.76µm)ColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Card Thickness	0.062" (1.57mm)
FeaturesBoard LockMounting TypeSurface MountTerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish ThicknessSupin (0.76µm)Contact TypeBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Number of Rows	2
Mounting TypeSurface MountTerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Pitch	0.050" (1.27mm)
TerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Features	Board Lock
Contact MaterialSpinodalContact MaterialGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Mounting Type	Surface Mount
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Termination	Solder
Contact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Contact Material	Spinodal
Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Contact Finish	Gold
Color Black Flange Feature - Operating Temperature -65°C ~ 200°C	Contact Finish Thickness	30µin (0.76µm)
Flange Feature-Operating Temperature-65°C ~ 200°C	Contact Type	Cantilever
Operating Temperature $-65^{\circ}\text{C} \sim 200^{\circ}\text{C}$	Color	Black
	Flange Feature	-
Report errors?	Operating Temperature	$-65^{\circ}C \sim 200^{\circ}C$
		Report errors?

FMB05DYFR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

FMB05DYFR Payment Methods



FMB05DYFR Shipping Methods



If you have any question about FMB05DYFR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com