



FMB25DYRR Information

Heisener.com

Part Number FMB25DYRR

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 50POS 0.050

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









Manufacturer Part Number FMB25DYRR Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 25 Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Board Lock, Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Spinodal Contact Finish Thickness 30µin (0.76µm) Contact Finish Thickness 30µin (0.76µm) Contact Type Cantilever Color Black Flange Feature - Operating Temperature -65°C ~ 200°C	TWD25DTKK Specifications	
Category Card Edge Connectors - Edgeboard Connectors Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 25 Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Board Lock, Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Spinodal Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Color Black Flange Feature - Operating Temperature - 65°C ~ 200°C	Manufacturer Part Number	FMB25DYRR
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 25 Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Board Lock, Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Spinodal Contact Finish Gold Contact Type Cantilever Color Black Flange Feature - Operating Temperature -65°C ~ 200°C	Manufacturer	Sullins Connector Solutions
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 25 Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Board Lock, Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Spinodal Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Cantilever Color Black Flange Feature - Operating Temperature -65°C ~ 200°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard Lock, Card ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard Lock, Card ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Package	-
GenderFemaleNumber of Positions/Bay/Row25Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard Lock, Card ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish Thickness30μin (0.76μm)Cotact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Series	-
Number of Positions/Bay/Row Solutions Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Board Lock, Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Spinodal Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Cantilever Color Black Flange Feature Operating Temperature 25 0.062" (1.57mm) Board Extender Board Lock, Card Extender Board Edge, Straddle Mount Solder Contact Material Spinodal Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Cantilever Color Black Flange Feature -65°C ~ 200°C	Card Type	Non Specified - Dual Edge
Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard Lock, Card ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard Lock, Card ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Number of Positions/Bay/Row	25
Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard Lock, Card ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Number of Positions	50
Pitch0.050" (1.27mm)FeaturesBoard Lock, Card ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Card Thickness	0.062" (1.57mm)
FeaturesBoard Lock, Card ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Number of Rows	2
Mounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Pitch	0.050" (1.27mm)
TerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Features	Board Lock, Card Extender
Contact MaterialSpinodalContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Mounting Type	Board Edge, Straddle Mount
Contact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Termination	Solder
Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type Cantilever Color Black Flange Feature - Operating Temperature $-65^{\circ}\text{C} \sim 200^{\circ}\text{C}$	Contact Material	Spinodal
Contact Type Color Black Flange Feature - Operating Temperature -65°C ~ 200°C	Contact Finish	Gold
Color Black Flange Feature - Operating Temperature -65°C ~ 200°C	Contact Finish Thickness	30μin (0.76μm)
Flange Feature - Grant	Contact Type	Cantilever
Operating Temperature $-65^{\circ}\text{C} \sim 200^{\circ}\text{C}$	Color	Black
	Flange Feature	-
Report errors?	Operating Temperature	-65°C ~ 200°C
		Report errors?

FMB25DYRR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FMB25DYRR Payment Methods



















FMB25DYRR Shipping Methods













If you have any question about FMB25DYRR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com