

FMB50DYFN

FMB50DYFN Information

| Contract to the second | FMB50DYFN Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 100POS .050 - For the pricing/inventory/lead time, please contact | |
|---|--|-----------------|
| For Reference Only | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



FMB50DYFN Specifications

| ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSulface MountYourder of AuterialSolderContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessGoldContact TypeGatileverContact TypeSulface MountContact TypeSolderContact TypeSolderContac | - | |
|---|-----------------------------|---|
| CategoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row50Number of Positions0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Nonting TypeSufface MountYourde TimishSolderContact FinishSolderContact Finish Thickness30µin (0.76µm)Contact TypeGatileverContact TypeSufface MountContact TypeSufface MountContact Finish ThicknessSolderContact Finish ThicknessSolderContact TypeGatileverContact TypeSufface MountContact TypeSufface MountContact TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderContact TypeCantileverContact TypeSolderContact TypeSolder | Manufacturer Part Number | FMB50DYFN |
| Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row50Number of Positions100Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountContact MaterialSolderContact Finish Thickness30jui (0.76µm)Contact Finish Thickness30juin (0.76µm)Contact TypeCantileverContact TypeCantileverColorBlackFlange Feature-Operating Temperature-5°C ~ 20°C | Manufacturer | Sullins Connector Solutions |
| Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row50Number of Positions100Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeCantileverContact TypeGoldContact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C | Category | Connectors, Interconnects |
| Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row50Number of Positions100Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountContact FinishSolderContact Finish Thickness30µin (0.76µm)Contact TypeCantileverContact TypeBlackFlange Feature-Operating Temperature-65°C ~ 200°C | | Card Edge Connectors - Edgeboard Connectors |
| Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row50Number of Positions100Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountContact MaterialSolderContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact TypeBlackFlange Feature-Forger Type65°C ~ 200°C | Package | - |
| GenderFemaleNumber of Positions/Bay/Row50Number of Positions100Card Thickness0.602° (1.57mm)Number of Rows2Pitch0.50° (1.27mm)Features-Mounting TypeSolderContact MaterialSindalContact FinishGoldContact Finish ThicknessGoldContact Finish ThicknessSindinorgContact Finish ThicknessSindinorgColage FeatureGalactFinage Feature-Operating Temperature65°C 200°C | Series | - |
| Number of Positions/Bay/Row50Number of Positions100Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountTerminationSolderContact MaterialGoldContact Finish Thickness30µin (0.76µm)Contact TypeGaltieverColorBlackFlange Feature-Operating Temperature-5°C ~ 200°C | Card Type | Non Specified - Dual Edge |
| Number of Positions100Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountTerminationSolderContact MaterialSpinodalContact Finish ThicknessGoldContact TypeCantileverColorBlackFlange Feature-Operating Temperature-55°C ~ 200°C | Gender | Female |
| Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountTerminationSolderContact MaterialSpinodalContact Finish ThicknessGoldContact TypeSurfaceMountColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C | Number of Positions/Bay/Row | 50 |
| Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountTerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C | Number of Positions | 100 |
| Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountTerminationSolderContact MaterialSpinodalContact Finish ThicknessGoldContact TypeSupin (0.76µm)ColorBlackFlange Feature-Operating Temperature-55°C ~ 200°C | Card Thickness | 0.062" (1.57mm) |
| Features-Mounting TypeSurface MountTerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish Thickness3µin (0.76µm)Contact TypeCantileverFlange Feature-Operating Temperatures-Solder- <t< td=""><td>Number of Rows</td><td>2</td></t<> | Number of Rows | 2 |
| Mounting TypeSurface MountTerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-55°C ~ 200°C | Pitch | 0.050" (1.27mm) |
| TerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C | Features | - |
| Contact MaterialSpinodalContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C | Mounting Type | Surface Mount |
| Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C | Termination | Solder |
| Contact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C | Contact Material | Spinodal |
| Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C | Contact Finish | Gold |
| ColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C | Contact Finish Thickness | 30µin (0.76µm) |
| Flange Feature-Operating Temperature-65°C ~ 200°C | Contact Type | Cantilever |
| Operating Temperature $-65^{\circ}\text{C} \sim 200^{\circ}\text{C}$ | Color | Black |
| | Flange Feature | - |
| Report errors? | Operating Temperature | -65°C ~ 200°C |
| | | Report errors? |

FMB50DYFN Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

FMB50DYFN Payment Methods



FMB50DYFN Shipping Methods



If you have any question about FMB50DYFN, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com