

FMB66DYFN

FMB66DYFN Information

Heisener.com	 FMB66DYFN Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 132POS .050 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



FMB66DYFN Specifications

ManufacturerSullins Connector SolutionsCardege Connectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Package-Stries-Card TypeMon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row66Number of Positions0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSulface MountYourde AtterialSolderContact FinishSolderContact Finish Thickness30µin (0.76µm)Contact TypeCantileverContact TypeSulface MountContact TypeSulface MountContact Finish ThicknessSolderContact Finish ThicknessSolderContact TypeCantileverFange Feature-Fange FeatureSulface MountColorBlack	-	
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row66Number of Positions0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountTerminationSolderContact Finish Thickness30µin (0.76µm)Contact Finish Thickness30µin (0.76µm)Contact TypeCantileverContact TypeSurface NotatContact TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderContact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Manufacturer Part Number	FMB66DYFN
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row66Number of Positions132Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeCantileverContact TypeCantileverContact TypeSurfaceContact TypeCantileverColorBlackFlange Feature-Operating Temperature-55°C ~ 200°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row66Number of Positions132Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountContact MaterialSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row66Number of Positions132Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountContact Finish ThicknessSolderContact Finish Thickness30µin (0.76µm)Contact TypeGataContact TypeSurface MountContact Finish ThicknessSolderContact TypeGataContact TypeSurface MountContact TypeSupin (0.76µm)Contact TypeGataContact TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderColorBlackFlange Feature-Operating Temperature-65°C 200°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row66Number of Positions132Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountContact MaterialSolderContact Finish ThicknessGoldContact TypeGupin (0.76µm)Contact TypeSurface MountContact TypeSurface MountContact TypeGoldContact TypeSurface MountContact TypeSurface MountColorBlackFauge Feature-Operating Temperature-65°C ~ 200°C	Package	-
GenderFemaleNumber of Positions/Bay/Row66Number of Positions132Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountContact MaterialSolderContact FinishGoldContact TypeGuid (0.76µm)Contact TypeSurface MountContact TypeGuid (0.76µm)Falage Feature-Operating Temperature-Operating Temperature-<	Series	-
Number of Positions/Bay/Row66Number of Positions132Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountTerminationSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-55°C ~ 200°C	Card Type	Non Specified - Dual Edge
Number of Positions132Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountTerminationSolderContact MaterialSoldaContact Finish ThicknessGoldContact TypeCantileverColorBlackFlange Feature-Operating Temperature65°C ~ 200°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountTerminationSolderContact MaterialSpinodalContact Finish ThicknessGoldContact TypeCantileverColorBlackFlange Feature-50°C ~ 200°C	Number of Positions/Bay/Row	66
Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountTerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Number of Positions	132
Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountTerminationSolderContact MaterialSpinodalContact Finish ThicknessGoldContact Finish ThicknessSupin (0.76µm)ColorBlackFlange Feature-Operating Temperature65°C ~ 200°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeSurface MountTerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeBlackFlange Feature-Operating Temperature-5°C ~ 200°C	Number of Rows	2
Mounting TypeSurface MountTerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-55°C ~ 200°C	Pitch	0.050" (1.27mm)
TerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Features	-
Contact MaterialSpinodalContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Mounting Type	Surface Mount
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Termination	Solder
Contact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Contact Material	Spinodal
Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Contact Finish	Gold
Color Black Flange Feature - Operating Temperature -65°C ~ 200°C	Contact Finish Thickness	30µin (0.76µm)
Flange Feature-Operating Temperature-65°C ~ 200°C	Contact Type	Cantilever
Operating Temperature $-65^{\circ}\text{C} \sim 200^{\circ}\text{C}$	Color	Black
	Flange Feature	-
Report errors?	Operating Temperature	-65°C ~ 200°C
		Report errors?

FMB66DYFN Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

FMB66DYFN Payment Methods



FMB66DYFN Shipping Methods



If you have any question about FMB66DYFN, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com