

FMB80DYFR

FMB80DYFR Information

Heisener.com	 FMB80DYFR Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 160POS .050 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



FMB80DYFR Specifications

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row80Number of Positions160Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeSulface MountContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessGoldContact TypeCantileverContact TypeBack	-	
CategoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row80Number of Positions/Bay/Row0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeSuface MountYontact MaterialSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverContact TypeGaldaceContact TypeSildeverContact TypeSolgerContact TypeSolgerContact TypeSolgerContact TypeCantileverContact TypeSolgerContact TypeSolgerContact TypeSolgerContact TypeSolgerContact TypeSolgerContact TypeCantileverContact TypeSolgerContact Type	Manufacturer Part Number	FMB80DYFR
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row80Number of Positions160Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeSurface MountContact MaterialSolderContact Finish Thickness30jui (0.76µm)Contact Finish Thickness30juin (0.76µm)Contact TypeCantileverContact TypeCantileverColorBlackFlange Feature-Operating Temperature-5°C ~ 200°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row80Number of Positions160Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeSurface MountContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeCantileverContact TypeCantileverColorBlackFlange Feature-Operating Temperature-55°C ~ 200°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row80Number of Positions/Bay/Row160Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeSurface MountContact FinishSolderContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact TypeEackColarBlackFlange Feature-Operating Temperature-65°C ~ 200°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row80Number of Positions160Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeSurface MountContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessGoldContact TypeCantileverColorBlackFlange Feature-Operating Temperature65°C ~ 200°C	Package	-
GenderFemaleNumber of Positions/Bay/Row80Number of Positions160Card Thickness0.602° (1.57mm)Number of Rows2Pitch0.50° (1.27mm)FeaturesBoard LockMounting TypeSolderContact MaterialSinodalContact FinishGoldContact Finish ThicknessGoldContact Finish ThicknessSinicolaContact Finish Thickness </td <td>Series</td> <td>-</td>	Series	-
Number of Positions/Bay/Row80Number of Positions160Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeSurface MountTerminationSolderContact MaterialGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-50°C ~ 200°C	Card Type	Non Specified - Dual Edge
Number of Positions160Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeSurface MountTerminationSolderContact MaterialSoldaContact Finish ThicknessGoldContact TypeCantileverColorBlackFlange Feature-Operating Temperature-55°C ~ 200°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeSurface MountTerminationSolderContact MaterialSpinodalContact Finish ThicknessGoldContact TypeSurlacveColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Number of Positions/Bay/Row	80
Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeSurface MountTerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Number of Positions	160
Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeSurface MountTerminationSolderContact MaterialSpinodalContact Finish ThicknessGoldContact TypeSupin (0.76µm)ColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Card Thickness	0.062" (1.57mm)
FeaturesBoard LockMounting TypeSurface MountTerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish ThicknessSupin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperatures-55°C ~ 200°C	Number of Rows	2
Mounting TypeSurface MountTerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-55°C ~ 200°C	Pitch	0.050" (1.27mm)
TerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Features	Board Lock
Contact MaterialSpinodalContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Mounting Type	Surface Mount
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Termination	Solder
Contact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Contact Material	Spinodal
Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Contact Finish	Gold
ColorBlackFlange Feature-Operating Temperature-65°C ~ 200°C	Contact Finish Thickness	30µin (0.76µm)
Flange Feature-Operating Temperature-65°C ~ 200°C	Contact Type	Cantilever
Operating Temperature $-65^{\circ}\text{C} \sim 200^{\circ}\text{C}$	Color	Black
	Flange Feature	-
Report errors?	Operating Temperature	-65°C ~ 200°C
		Report errors?

FMB80DYFR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

FMB80DYFR Payment Methods



FMB80DYFR Shipping Methods



If you have any question about FMB80DYFR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com