

FMC13DRAN

FMC13DRAN Information

Heisener.com	FMC13DRAN Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 26POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



FMC13DRAN Specifications

ManufacturerSullins Connector SolutionsCardegoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row13Number of Positions0.62° (1.57mm)Number of Rows2Pitch0.100° (2.54mm)Features-Mounting Type13Contact FinishSolderContact Finish Thickness0.62° (1.57mm)Contact Finish ThicknessSolderContact Finish ThicknessSolderContact Finish ThicknessSolderContact TypeGuldContact TypeSull BellowsContact TypeSolgerContact TypeSolgerCont	-	
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row13Number of Positions26Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 200°C	Manufacturer Part Number	FMC13DRAN
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row13Number of Positions26Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeFull BellowsContact Type50°C ~ 200°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row13Number of Positions26Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact FinishGoldContact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 200°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row13Number of Positions26Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact Finish ThicknessSolderContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeGreenFlange Feature-Operating Temperature65°C ~ 200°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row13Number of Positions26Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact Finish ThicknessGoldContact TypeSupin (0.76µm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 200°C	Package	-
Gender Female Number of Positions/Bay/Row 13 Number of Positions 26 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Full Bellows Color Green Flange Feature - Operating Temperature -	Series	-
Number of Positions/Bay/Row13Number of Positions26Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact FinishGoldContact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-S°C ~ 200°C	Card Type	Non Specified - Dual Edge
Number of Positions 26 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type - Mounting Type Through Hole, Right Angle Contact Material Solder Contact Finish Gold Contact Finish Thickness Gold Contact Type Full Bellows Color Green Flange Feature - Operating Temperature -65°C ~ 200°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish ThicknessSupin (0.76µm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 200°C	Number of Positions/Bay/Row	13
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 200°C	Number of Positions	26
Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialSpinodalContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)ColorFull BellowsColorGreenFlange Feature-Operating Temperature-55°C ~ 200°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-55°C ~ 200°C	Number of Rows	2
Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-55°C ~ 200°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialSpinodalContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 200°C	Features	-
Contact MaterialSpinodalContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 200°C	Mounting Type	Through Hole, Right Angle
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 200°C	Termination	Solder
Contact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 200°C	Contact Material	Spinodal
Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 200°C	Contact Finish	Gold
Color Green Flange Feature - Operating Temperature -65°C ~ 200°C	Contact Finish Thickness	30µin (0.76µm)
Flange Feature-Operating Temperature-65°C ~ 200°C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 200^{\circ}\text{C}$	Color	Green
	Flange Feature	-
Report errors?	Operating Temperature	$-65^{\circ}\mathrm{C} \sim 200^{\circ}\mathrm{C}$
		Report errors

FMC13DRAN Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

FMC13DRAN Payment Methods



FMC13DRAN Shipping Methods



If you have any question about FMC13DRAN, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com