

FMC19DRES-S734

uote

FMC19DRES-S734 Information

Heisener.com	Part Number Manufacturer Category Description Package	FMC19DRES-S734 Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 38POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Qu

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



FMC19DRES-S734 Specifications

ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row19Number of Positions38Card Type0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Number of Rows9Features-Mounting TypePanel MountContact FinishSolder Eyelet(s)Contact Finish Thickness0.0jui (0.76µm)Contact TypeSilo (0.76µm)Contact TypeSilo (0.76µm)Contact TypeSilo (0.76µm)Contact Finish ThicknessSilo (0.76µm)Contact TypeFeallenssContact TypeSilo (0.76µm)Contact TypeSilo (0.76µm)		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row19Number of Positions38Card Thickness0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact Finish Thickness30µin (0.76µm)Contact TypeGoldContact TypeSolup (0.76µm)Contact TypeSolup (0.76µm)Contact Finish Thickness30µin (0.76µm)Contact TypeFeallowsContact TypeFull BellowsColorGreenFlage FeatureSick Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 20°C	Manufacturer Part Number	FMC19DRES-S734
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row19Number of Positions38Card Thickness0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialSpinodalContact Finish Thickness30µin (0.76µm)Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 200°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row19Number of Positions38Card Thickness0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeGoldContact TypeSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaCoperating Temperaturesic% ~ 200°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row19Number of Positions38Card Thickness0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountContact FinishSolder Eyelet(s)Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating TemperatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) Dia		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row19Number of Positions38Card Thickness0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact Finish ThicknessGoldContact TypeGujún (0.76µm)Contact TypeFeil BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 200°C	Package	-
GenderFemaleNumber of Positions/Bay/Row19Number of Positions38Card Thickness0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 200°C	Series	-
Number of Positions/Bay/Row19Number of Positions38Card Thickness0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact FinishGoldContact TypeSupin (0.76µm)Contact TypeSupin (0.76µm)ColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 200°C	Card Type	Non Specified - Dual Edge
Number of Positions38Card Thickness0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialGoldContact FinishGoldContact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 200°C	Gender	Female
Card Thickness0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialSpinodalContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 200°C	Number of Positions/Bay/Row	19
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialSpinodalContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 200°C	Number of Positions	38
Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialSpinodalContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 200°C	Card Thickness	0.031" (0.79mm)
Features-Mounting TypePanel MountMounting TypeSolder Eyelet(s)Contact MaterialSpinodalContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 200°C	Number of Rows	2
Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialSpinodalContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 200°C	Pitch	0.100" (2.54mm)
TerminationSolder Eyelet(s)Contact MaterialSpinodalContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 200°C	Features	-
Contact MaterialSpinodalContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 200°C	Mounting Type	Panel Mount
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 200°C	Termination	Solder Eyelet(s)
Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 200°C	Contact Material	Spinodal
Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 200°C	Contact Finish	Gold
ColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 200°C	Contact Finish Thickness	30µin (0.76µm)
Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 200°C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}C \sim 200^{\circ}C$	Color	Green
	Flange Feature	Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 200°C
•		Report errors?

FMC19DRES-S734 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

FMC19DRES-S734 Payment Methods



FMC19DRES-S734 Shipping Methods



If you have any question about FMC19DRES-S734, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com