



FMN.3M.330.XLCT Information



For Reference Only

Part Number FMN.3M.330.XLCT

Manufacturer LEMO

Category Connectors, Interconnects

Circular Connectors

Description CONN INLINE PLUG 30PIN CRIMP

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FMN.3M.330.XLCT Specifications

Manufacturer Part NumberFMN.3M.330.XLCTManufacturerLEMOCategoryConnectors, InterconnectsPackage-Series3MConnector TypePlug, Male PinsNumber of Positions30Shell Size - Insert330Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating3.5AReport errors?		
CategoryConnectors, InterconnectsPackage-Series3MConnector TypePlug, Male PinsNumber of Positions30Shell Size - Insert330Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating3.5A	Manufacturer Part Number	FMN.3M.330.XLCT
Circular Connectors Package - Series 3M Connector Type Plug, Male Pins Number of Positions 30 Shell Size - Insert 330 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection NP68 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Urrent Rating 3.5A	Manufacturer	LEMO
Package - Series 3M Connector Type Plug, Male Pins Number of Positions 30 Shell Size - Insert 330 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP68 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Condact Finish Gold Features Shielded Voltage - Rated Current Rating 3.5A	Category	Connectors, Interconnects
Series3MConnector TypePlug, Male PinsNumber of Positions30Shell Size - Insert330Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating3.5A		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions30Shell Size - Insert330Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating3.5A	Package	-
Number of Positions30Shell Size - Insert330Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating3.5A	Series	3M
Shell Size - Insert330Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating3.5A	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP68 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 3.5A	Number of Positions	30
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating3.5A	Shell Size - Insert	330
Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP68 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 3.5A	Shell Size, MIL	-
Fastening Type Orientation Ingress Protection Shell Material, Finish Contact Finish Contact Finish Features Shielded Voltage - Rated Current Rating Threaded N (Normal) Inference N (Normal) Inference Aluminum Alloy, Nickel Plated Gold Shielded - Current Rating 3.5A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection IP68 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 3.5A	Termination	Crimp
Ingress Protection IP68 - Dust Tight, Waterproof Aluminum Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 3.5A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating 3.5A	Orientation	N (Normal)
Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 3.5A	Ingress Protection	IP68 - Dust Tight, Waterproof
Features Shielded Voltage - Rated - Current Rating 3.5A	Shell Material, Finish	Aluminum Alloy, Nickel Plated
Voltage - Rated - Current Rating 3.5A	Contact Finish	Gold
Current Rating 3.5A	Features	Shielded
	Voltage - Rated	-
Report errors?	Current Rating	3.5A
		Report errors?

FMN.3M.330.XLCT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FMN.3M.330.XLCT Payment Methods



















FMN.3M.330.XLCT Shipping Methods













If you have any question about FMN.3M.330.XLCT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com