

# FNQ-R-25

## **FNQ-R-25 Information**



For Reference Only

Part Number	FNQ-R-25	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE CARTRIDGE 25A 600VAC 5AG	
Package	5AG, 10mm x 38.1mm	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

#### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### **FNQ-R-25** Specifications

Manufacturer Part Number FNQ-R-25   Manufacturer Eaton   Category Circuit Protection   Electrical, Specialty Fuses   Package SAG, 10mm x 38.1mm   Series Limitron? FNQ-R   Fuse Type Catridge   Current Rating 25A   Voltage Rating - AC 600V   Voltage Rating - DC -   Response Time Slow   Applications Electrical, Industrial   Features -   Class CC   Approvals CE, CSA, UL   Operating Temperature -   Breaking Capacity @ Rated Voltage 200kA   Mounting Type Holder   Stacy (Lass SAG, 10mm x 38.1mm		
CategoryCircuit ProtectionElectrical, Specialty FusesPackage5AG, 10mm x 38.1mmSeriesLimitron? FNQ-RFuse TypeCartridgeCurrent Rating55AVoltage Rating - AC600VVoltage Rating - DCSlowResponse TimeSlowApplicationsElectrical, IndustrialFatures-ClassCCApprovalsCE, CSA, ULOperating Paneture300KAFaturg Capacity @ Rated Voltage-ApprovalsCE, CSA, ULOperating Type-Fackage / CaseSGA (10mm x 38.1mm)Size / Dimension5AG, 10mm x 38.10mm, 38.10mm, 58.10mm)	Manufacturer Part Number	FNQ-R-25
PackageElectrical, Specialty FusesPackageSAG, 10mm x 38.1mmSeriesLimitron? FNQ-RFuse TypeCartridgeCurrent Rating25AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature300KABreaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseSAG, 10mm x 38.1mmSize / Dimension0.406" Diax 1.500" L (10.30mm x 38.10mm)	Manufacturer	Eaton
Package5AG, 10mm x 38.1mmSeriesLimitron? FNQ-RFuse TypeCartridgeCurrent Rating25AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassCCApprovals-Operating Temperature-Operating Temperature200kAMounting TypeBickerPackage / Case5AG, 10mm x 38.1mmSize / Dinension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Category	Circuit Protection
SeriesLimitron? FNQ-RFuse TypeCartridgeCurrent Rating25AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassCCApprovalsElectroal, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseSAG, 10mm x 38.10mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating25AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassCCApprovalsElectrosA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseSAG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Package	5AG, 10mm x 38.1mm
Current Rating25AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Series	Limitron? FNQ-R
Voltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Fuse Type	Cartridge
Voltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseSAG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Current Rating	25A
Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Voltage Rating - AC	600V
ApplicationsElectrical, IndustrialFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Voltage Rating - DC	-
Features-Features-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Response Time	Slow
ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Applications	Electrical, Industrial
ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Features	-
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Class	CC
Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Approvals	CE, CSA, UL
Mounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Operating Temperature	-
Package / Case 5AG, 10mm x 38.1mm   Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Mounting Type	Holder
	Package / Case	5AG, 10mm x 38.1mm
Report errors'	Size / Dimension	0.406" Dia x 1.500" L (10.30mm x 38.10mm)
		Report error

#### **FNQ-R-25** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

#### Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about FNQ-R-25, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com