

FNQ-R-3-2/10

FNQ-R-3-2/10 Information



For Reference Only

Part Number	FNQ-R-3-2/10	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE CARTRIDGE 3.2A 600VAC 5AG	
Package	5AG, 10mm x 38.1mm	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



FNQ-R-3-2/10 Specifications

ManufacturerEatonCategoryCircuit ProtectionElectrical, Specialty FusesPackageSAG, 10mm x 38.1mmSeriesLimitron? FNQ-RFuse TypeCartridgeCurrent Rating3.2AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseSAG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)		
CategoryCircuit ProtectionElectrical, Specialty FusesPackage5AG, 10mm x 38.1mmSeriesLimitron? FNQ-RFuse TypeCartridgeCurrent Rating3.2AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature200kABreaking Capacity @ Rated Voltage5AG, 10mm x 38.1mmSize / Dimension5AG, 10mm x 38.10mm, 38.10mm	Manufacturer Part Number	FNQ-R-3-2/10
ConstraintElectrical, Specialty FusesPackage5AG, 10mm x 38.1mmSeriesLimitron? FNQ-RFuse TypeCartridgeCurrent Rating3.2AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Manufacturer	Eaton
Package5AG, 10mm x 38.1mmSeriesLimitron? FNQ-RFuse TypeCartridgeCurrent Rating3.2AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassCCApprovalsCE, CSA, ULOperating Type-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseSAG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Category	Circuit Protection
SeriesLimitron? FNQ-RFuse TypeCartridgeCurrent Rating3.2AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseSAG, 10mm x 38.10mm, 38.10mm, set.00mm to the		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating3.2AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseSAG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Package	5AG, 10mm x 38.1mm
Current Rating3.2ACurrent Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseSAG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Series	Limitron? FNQ-R
Voltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Fuse Type	Cartridge
Voltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Current Rating	3.2A
Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Voltage Rating - AC	600V
ApplicationsElectrical, IndustrialFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseSAG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Voltage Rating - DC	-
Features-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Response Time	Slow
ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Applications	Electrical, Industrial
ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Features	-
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Class	CC
Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Approvals	CE, CSA, UL
Mounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Operating Temperature	-
Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Mounting Type	Holder
	Package / Case	5AG, 10mm x 38.1mm
Report errors?	Size / Dimension	0.406" Dia x 1.500" L (10.30mm x 38.10mm)
		Report errors?

FNQ-R-3-2/10 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

FNQ-R-3-2/10 Payment Methods



FNQ-R-3-2/10 Shipping Methods



If you have any question about FNQ-R-3-2/10, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com