

## FNQ-R-4/10 Information



For Reference Only

Part Number FNQ-R-4/10

Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 400MA 600VAC 5AG

Package 5AG, 10mm x 38.1mm

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## FNQ-R-4/10 Specifications

Manufacturer Part NumberFNQ-R-4/10ManufacturerEatonCategoryCircuit ProtectionBeckage5AG, 10mm x 38.1mmSeriesLimitron? FNQ-RFuse TypeCartridgeCurrent Rating400mAVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)		
Category Electrical, Specialty Fuses  Package SAG, 10mm x 38.1mm Series Limitron? FNQ-R Fuse Type Cartridge Current Rating 400mA Voltage Rating - AC Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class CC Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  Circuit Protection Electrical, Specialty Fuses SAG, 10mm x 38.1mm Size / Dimension  Circuit Protection Electrical, Industrial Capacity @ Rated Voltage Holder SAG, 10mm x 38.1mm Size / Dimension  Circuit Protection Electrical, Specialty Fuses Size / Dimension  Capacity Power Size / Dimension  Circuit Protection Size / Dimension  Capacity Puses Size / Dimension  Circuit Protection Size / Dimension  Capacity Puses Size / Dimension  Circuit Protection Size / Dimension  Capacity Puses Size / Dimension  Circuit Protection Size / Dimension  Capacity Puses Size / Dimension  Circuit Protection Size / Dimension  Capacity Puses Size / Dimension  Circuit Protection Size / Di	Manufacturer Part Number	FNQ-R-4/10
Electrical, Specialty Fuses  Package 5AG, 10mm x 38.1mm  Series Limitron? FNQ-R  Fuse Type Cartridge  Current Rating 400mA  Voltage Rating - AC 600V  Voltage Rating - DC - Response Time Slow  Applications Electrical, Industrial  Features - Class CC  Approvals CE, CSA, UL  Operating Temperature - Breaking Capacity @ Rated Voltage 200kA  Mounting Type Holder  Package / Case 5AG, 10mm x 38.1mm  Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Manufacturer	Eaton
Package         5AG, 10mm x 38.1mm           Series         Limitron? FNQ-R           Fuse Type         Cartridge           Current Rating         400mA           Voltage Rating - AC         600V           Voltage Rating - DC         -           Response Time         Slow           Applications         Electrical, Industrial           Features         -           Class         CC           Approvals         CE, CSA, UL           Operating Temperature         -           Breaking Capacity @ Rated Voltage         200kA           Mounting Type         Holder           Package / Case         5AG, 10mm x 38.1mm           Size / Dimension         0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Category	Circuit Protection
SeriesLimitron? FNQ-RFuse TypeCartridgeCurrent Rating400mAVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating400mAVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Package	5AG, 10mm x 38.1mm
Current Rating Voltage Rating - AC 600V  Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class CC Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  400mA 400mA 600V  CE, CSA CC CE, CSA CC	Series	Limitron? FNQ-R
Voltage Rating - AC  Voltage Rating - DC  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  CC  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  600V  6	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Slow  Applications Electrical, Industrial  Features - Class CC  Approvals CE, CSA, UL  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  Size / Dimension  Slow  Clow  Electrical, Industrial  CC  CC  Approvals - CC  AC  AC  AC  AC  AC  AC  AC  AC  A	Current Rating	400mA
Response Time  Applications  Electrical, Industrial  Features  - Class  CC  Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  5AG, 10mm x 38.1mm  Size / Dimension  Slow  Electrical, Industrial  CC  CC  4D  CC  APPOVA  CE, CSA, UL  - Breaking Capacity @ Rated Voltage  AN  AN  AN  AN  AN  AN  AN  AN  AN  A	Voltage Rating - AC	600V
Applications Electrical, Industrial Features - Class CC Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Voltage Rating - DC	-
Features - Class CC Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Response Time	Slow
Class CC Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension O.406" Dia x 1.500" L (10.30mm x 38.10mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Features	-
Operating Temperature - 200kA Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Class	CC
Breaking Capacity @ Rated Voltage 200kA  Mounting Type Holder  Package / Case 5AG, 10mm x 38.1mm  Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Operating Temperature	-
Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Mounting Type	Holder
	Package / Case	5AG, 10mm x 38.1mm
Report errors?	Size / Dimension	0.406" Dia x 1.500" L (10.30mm x 38.10mm)
		Report errors?

### FNQ-R-4/10 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### FNQ-R-4/10 Payment Methods



















### FNQ-R-4/10 Shipping Methods













If you have any question about FNQ-R-4/10, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com