

## FOD8384

### **FOD8384 Information**



# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### **FOD8384** Specifications

Manufacturer Part NumberFOD8384ManufacturerFairchild/ON SemiconductorCategoryIsolatorsPackageGate DriversPackage6-SOIC (0.346", 8.80mm Width) 5 LeadsSeries-FechnologyOptical CouplingNumber of Channels1Voltage - IsolationSoloVrmsCommon Mode Transient Immunity (Min)StkVµsPropagation Delay tpLH / tpHL (Max)210ns, 210nsPulse Width Distortion (Max)65nsCurrent - Output High, Low2.5A, 2.5ACurrent - Peak Output3AVoltage - Forward (Vf) (Typ)1.43VCurrent - DC Forward (If (Max)25mA
CategoryIsolatorsCategoryIsolators - Gate DriversPackage6-SOIC (0.346", 8.80mm Width) 5 LeadsPackage-Series-FechnologyOptical CouplingNumber of Channels1Voltage - Isolation5000VrmsCommon Mode Transient Immunity (Min)35kV/µsPropagation Delay tpLH / tpHL (Max)210ns, 210nsPulse Width Distortion (Max)65nsRise / Fall Time (Typ)35ns, 25nsCurrent - Output High, Low2.5A, 2.5ACurrent - Peak Output3AVoltage - Forward (Vf) (Typ)1.43V
InstancePackage6-SOIC (0.346", 8.80mm Width) 5 LeadsPackage-Series-FechnologyOptical CouplingNumber of Channels1Voltage - Isolation5000VrmsCommon Mode Transient Immunity (Min)35kV/µsPropagation Delay tpLH / tpHL (Max)210ns, 210nsPulse Width Distortion (Max)65nsRise / Fall Time (Typ)35ns, 25nsCurrent - Output High, Low2.5A, 2.5ACurrent - Peak Output3AVoltage - Forward (Vf) (Typ)1.43V
Package6-SOIC (0.346", 8.80mm Width) 5 LeadsGeries-TechnologyOptical CouplingNumber of Channels1Voltage - Isolation5000VrmsCommon Mode Transient Immunity (Min)35kV/µsPropagation Delay tpLH / tpHL (Max)210ns, 210nsPulse Width Distortion (Max)65nsRise / Fall Time (Typ)35ns, 25nsCurrent - Output High, Low2.5A, 2.5ACurrent - Peak Output3AVoltage - Forward (Vf) (Typ)1.43V
Series-FechnologyOptical CouplingNumber of Channels1Voltage - Isolation5000VrmsCommon Mode Transient Immunity (Min)35kV/µsPropagation Delay tpLH / tpHL (Max)210ns, 210nsPulse Width Distortion (Max)65nsRise / Fall Time (Typ)35ns, 25nsCurrent - Output High, Low2.5A, 2.5ACurrent - Peak Output3AVoltage - Forward (Vf) (Typ)1.43V
FechnologyOptical CouplingNumber of Channels1Voltage - Isolation5000VrmsCommon Mode Transient Immunity (Min)35kV/μsPropagation Delay tpLH / tpHL (Max)210ns, 210nsPulse Width Distortion (Max)65nsRise / Fall Time (Typ)35ns, 25nsCurrent - Output High, Low2.5A, 2.5ACurrent - Peak Output3AVoltage - Forward (Vf) (Typ)1.43V
Number of Channels1Voltage - Isolation5000VrmsCommon Mode Transient Immunity (Min)35kV/µsPropagation Delay tpLH / tpHL (Max)210ns, 210nsPulse Width Distortion (Max)65nsRise / Fall Time (Typ)35ns, 25nsCurrent - Output High, Low2.5A, 2.5ACurrent - Peak Output3AVoltage - Forward (Vf) (Typ)1.43V
Woltage - Isolation5000VrmsCommon Mode Transient Immunity (Min)35kV/µsPropagation Delay tpLH / tpHL (Max)210ns, 210nsPulse Width Distortion (Max)65nsRise / Fall Time (Typ)35ns, 25nsCurrent - Output High, Low2.5A, 2.5ACurrent - Peak Output3AVoltage - Forward (Vf) (Typ)1.43V
Common Mode Transient Immunity (Min)35kV/µsPropagation Delay tpLH / tpHL (Max)210ns, 210nsPulse Width Distortion (Max)65nsRise / Fall Time (Typ)35ns, 25nsCurrent - Output High, Low2.5A, 2.5ACurrent - Peak Output3AVoltage - Forward (Vf) (Typ)1.43V
Propagation Delay tpLH / tpHL (Max)210ns, 210nsPulse Width Distortion (Max)65nsRise / Fall Time (Typ)35ns, 25nsCurrent - Output High, Low2.5A, 2.5ACurrent - Peak Output3AVoltage - Forward (Vf) (Typ)1.43V
Pulse Width Distortion (Max)65nsRise / Fall Time (Typ)35ns, 25nsCurrent - Output High, Low2.5A, 2.5ACurrent - Peak Output3AVoltage - Forward (Vf) (Typ)1.43V
Rise / Fall Time (Typ)35ns, 25nsCurrent - Output High, Low2.5A, 2.5ACurrent - Peak Output3AVoltage - Forward (Vf) (Typ)1.43V
Current - Output High, Low2.5A, 2.5ACurrent - Peak Output3AVoltage - Forward (Vf) (Typ)1.43V
Current - Peak Output3AVoltage - Forward (Vf) (Typ)1.43V
Voltage - Forward (Vf) (Typ) 1.43V
Current - DC Forward (If) (Max) 25mA
Voltage - Supply 15 V ~ 30 V
Departing Temperature $-40^{\circ}\text{C} \sim 100^{\circ}\text{C}$
Mounting Type Surface Mount
Package / Case 6-SOIC (0.346", 8.80mm Width) 5 Leads
Supplier Device Package 5-SOP
Approvals UL
Report errors?

#### **FOD8384** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE GUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about FOD8384, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com