

### FP24-500 Information



For Reference Only

Part Number FP24-500

Manufacturer Triad Magnetics

Category Transformers
Power Transformers

**Description** XFRMR LAMINATED 12VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **FP24-500 Specifications**

Manufacturer Part Number         FP24-500           Manufacturer         Triad Magnetics           Category         Transformers           Power Transformers         Power Transformers           Series         FP           Type         Laminated Core           Voltage - Primary         115V, 230V           Voltage - Secondary (Full Load)         Parallel 12V, Series 24V           Current - Output (Max)         Parallel 1A, Series 500mA           Primary Winding(s)         Dual           Secondary Winding(s)         Dual           Center Tap         No           Power - Max         12 VA           Mounting Type         Through Hole           Termination Style         PC Pin           Size / Dimension         63.50mm L x 50.80mm W           Height - Seated (Max)         26.97mm           Voltage - Isolation         2000Vrms           Weight         0.688 lb (312.07g)		
Category         Transformers           Power Transformers           Package         -           Series         FP           Type         Laminated Core           Voltage - Primary         115V, 230V           Voltage - Secondary (Full Load)         Parallel 12V, Series 24V           Current - Output (Max)         Parallel 1A, Series 500mA           Primary Winding(s)         Dual           Secondary Winding(s)         Dual           Center Tap         No           Power - Max         12 VA           Mounting Type         Through Hole           Termination Style         PC Pin           Size / Dimension         63.50mm L x 50.80mm W           Height - Seated (Max)         26.97mm           Voltage - Isolation         2000Vrms           Weight         0.688 lb (312.07g)	Manufacturer Part Number	FP24-500
Package         Power Transformers           Series         FP           Type         Laminated Core           Voltage - Primary         115V, 230V           Voltage - Secondary (Full Load)         Parallel 12V, Series 24V           Current - Output (Max)         Parallel 1A, Series 500mA           Primary Winding(s)         Dual           Secondary Winding(s)         Dual           Center Tap         No           Power - Max         12 VA           Mounting Type         Through Hole           Termination Style         PC Pin           Size / Dimension         63.50mm L x 50.80mm W           Height - Seated (Max)         26.97mm           Voltage - Isolation         2000Vrms           Weight         0.688 lb (312.07g)	Manufacturer	Triad Magnetics
Package         -           Series         FP           Type         Laminated Core           Voltage - Primary         115V, 230V           Voltage - Secondary (Full Load)         Parallel 12V, Series 24V           Current - Output (Max)         Parallel 1A, Series 500mA           Primary Winding(s)         Dual           Secondary Winding(s)         Dual           Center Tap         No           Power - Max         12 VA           Mounting Type         Through Hole           Termination Style         PC Pin           Size / Dimension         63.50mm L x 50.80mm W           Height - Seated (Max)         26.97mm           Voltage - Isolation         2000Vrms           Weight         0.688 lb (312.07g)	Category	Transformers
SeriesFPTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 12V, Series 24VCurrent - Output (Max)Parallel 1A, Series 500mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension63.50mm L x 50.80mm WHeight - Seated (Max)26.97mmVoltage - Isolation2000VrmsWeight0.688 lb (312.07g)		Power Transformers
Type Laminated Core  Voltage - Primary 115V, 230V  Voltage - Secondary (Full Load) Parallel 12V, Series 24V  Current - Output (Max) Parallel 1A, Series 500mA  Primary Winding(s) Dual  Secondary Winding(s) Dual  Center Tap No Power - Max 12 VA  Mounting Type Through Hole  Termination Style PC Pin  Size / Dimension 63.50mm L x 50.80mm W  Height - Seated (Max) 26.97mm  Voltage - Isolation 2000Vrms  Weight 0.688 lb (312.07g)	Package	-
Voltage - Primary  Voltage - Secondary (Full Load)  Parallel 12V, Series 24V  Current - Output (Max)  Parallel 1A, Series 500mA  Primary Winding(s)  Dual  Secondary Winding(s)  Dual  Center Tap  No  Power - Max  12 VA  Mounting Type  Through Hole  Termination Style  PC Pin  Size / Dimension  63.50mm L x 50.80mm W  Height - Seated (Max)  Voltage - Isolation  Voltage - Isolation  Weight	Series	FP
Voltage - Secondary (Full Load)  Current - Output (Max)  Parallel 12V, Series 24V  Parallel 1A, Series 500mA  Primary Winding(s)  Dual  Secondary Winding(s)  Dual  Center Tap  No  Power - Max  12 VA  Mounting Type  Through Hole  Termination Style  Size / Dimension  63.50mm L x 50.80mm W  Height - Seated (Max)  Voltage - Isolation  Voltage - Isolation  Weight  Parallel 12V, Series 24V  Poul Secondary Series 24V  Parallel 12V, Series 24V  Poul Secondary Series 24V  Pou	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 12 VA Mounting Type Through Hole Termination Style Size / Dimension Size / Dimension Woltage - Isolation Voltage - Isolation Parallel 1A, Series 500mA Dual Pual Pual Poul Poul Poul Poul Poul Poul Poul Pou	Voltage - Primary	115V, 230V
Primary Winding(s)  Secondary Winding(s)  Dual  Center Tap  No  Power - Max  12 VA  Mounting Type  Through Hole  Termination Style  PC Pin  Size / Dimension  63.50mm L x 50.80mm W  Height - Seated (Max)  Voltage - Isolation  Weight  Dual  No  2000Vrms  Dual  No  0.688 lb (312.07g)	Voltage - Secondary (Full Load)	Parallel 12V, Series 24V
Secondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension63.50mm L x 50.80mm WHeight - Seated (Max)26.97mmVoltage - Isolation2000VrmsWeight0.688 lb (312.07g)	Current - Output (Max)	Parallel 1A, Series 500mA
Center Tap  Power - Max  12 VA  Mounting Type  Through Hole  Termination Style  PC Pin  Size / Dimension  63.50mm L x 50.80mm W  Height - Seated (Max)  Voltage - Isolation  2000Vrms  Weight  No  12 VA  Through Hole  PC Pin  63.50mm L x 50.80mm W  26.97mm  2000Vrms	Primary Winding(s)	Dual
Power - Max  Mounting Type  Through Hole  Termination Style  PC Pin  Size / Dimension  63.50mm L x 50.80mm W  Height - Seated (Max)  Voltage - Isolation  Voltage - Isolation  Weight  12 VA  PC Pin  63.50mm L x 50.80mm W  26.97mm  2000Vrms  0.688 lb (312.07g)	Secondary Winding(s)	Dual
Mounting TypeThrough HoleTermination StylePC PinSize / Dimension63.50mm L x 50.80mm WHeight - Seated (Max)26.97mmVoltage - Isolation2000VrmsWeight0.688 lb (312.07g)	Center Tap	No
Termination Style PC Pin Size / Dimension 63.50mm L x 50.80mm W Height - Seated (Max) 26.97mm Voltage - Isolation 2000Vrms Weight 0.688 lb (312.07g)	Power - Max	12 VA
Size / Dimension 63.50mm L x 50.80mm W  Height - Seated (Max) 26.97mm  Voltage - Isolation 2000Vrms  Weight 0.688 lb (312.07g)	Mounting Type	Through Hole
Height - Seated (Max)  Voltage - Isolation  Weight  26.97mm  2000Vrms  0.688 lb (312.07g)	Termination Style	PC Pin
Voltage - Isolation 2000Vrms Weight 0.688 lb (312.07g)	Size / Dimension	63.50mm L x 50.80mm W
Weight 0.688 lb (312.07g)	Height - Seated (Max)	26.97mm
	Voltage - Isolation	2000Vrms
Report errors?	Weight	0.688 lb (312.07g)
		Report errors?

### FP24-500 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## FP24-500 Payment Methods





















## **FP24-500 Shipping Methods**













If you have any question about FP24-500, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com