

Heisener.com

FRCIR00RFS-14S-8S-F80-T12

FRCIR00RFS-14S-8S-F80-T12 Information

Part Number FRCIR00RFS-14S-8S-F80-T12

Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 8POS PNL MNT SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FRCIR00RFS-14S-8S-F80-T12 Specifications

Manufacturer Part Number Manufacturer Category Connectors, Interconnects Circular Connectors Package Package Series MIL-DTL-5015, CIR Connector Type Receptacle, Female Sockets Number of Positions Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Flame Retardant Voltage - Rated Current Rating 7,5A Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert14S-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesFlame RetardantVoltage - Rated-Current Rating7.5A	Manufacturer Part Number	FRCIR00RFS-14S-8S-F80-T12
Package-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert14S-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesFlame RetardantVoltage - Rated-Current Rating7.5A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert14S-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesFlame RetardantVoltage - Rated-Current Rating7.5A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert14S-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesFlame RetardantVoltage - Rated-Current Rating7.5A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert14S-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesFlame RetardantVoltage - Rated-Current Rating7.5A	Package	-
Number of Positions8Shell Size - Insert14S-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesFlame RetardantVoltage - Rated-Current Rating7.5A	Series	MIL-DTL-5015, CIR
Shell Size - Insert14S-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesFlame RetardantVoltage - Rated-Current Rating7.5A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Flame Retardant Voltage - Rated - Current Rating 7.5A	Number of Positions	8
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesFlame RetardantVoltage - Rated-Current Rating7.5A	Shell Size - Insert	14S-8
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Flame Retardant Voltage - Rated - Current Rating 7.5A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Flame Retardant Voltage - Rated - Current Rating 7.5A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Flame Retardant Voltage - Rated - Current Rating 7.5A	Termination	Crimp
Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Flame Retardant Voltage - Rated - Current Rating 7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Flame Retardant Voltage - Rated - Current Rating 7.5A	Orientation	N (Normal)
Contact Finish Gold Features Flame Retardant Voltage - Rated - Current Rating 7.5A	Ingress Protection	Environment Proof
Features Flame Retardant Voltage - Rated - Current Rating 7.5A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated - Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	Flame Retardant
-	Voltage - Rated	-
Report errors?	Current Rating	7.5A
1		Report errors?

FRCIR00RFS-14S-8S-F80-T12 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FRCIR00RFS-14S-8S-F80-T12 Payment Methods



















FRCIR00RFS-14S-8S-F80-T12 Shipping Methods













If you have any question about FRCIR00RFS-14S-8S-F80-T12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com