

Heisener.com

# FRCIR020R-24-10S-F80

### FRCIR020R-24-10S-F80 Information

Part Number FRCIR020R-24-10S-F80

Manufacturer ITT Cannon, LLC

**Category** Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 7POS PNL MNT W/SCKTS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### FRCIR020R-24-10S-F80 Specifications

Manufacturer Part NumberFRCIR020R-24-10S-F80ManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert24-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating46A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert24-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating46A	Manufacturer Part Number	FRCIR020R-24-10S-F80
Package-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert24-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating46A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert24-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating46A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert24-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating46A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert24-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating46A	Package	-
Number of Positions7Shell Size - Insert24-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating46A	Series	MIL-DTL-5015, CIR
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Flame Retardant Voltage - Rated Current Rating 46A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating  46A	Number of Positions	7
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating46A	Shell Size - Insert	24-10
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 46A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 46A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 46A	Termination	Crimp
Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 46A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Silver Features Flame Retardant Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver Flame Retardant 46A	Orientation	N (Normal)
Contact Finish  Features  Flame Retardant  Voltage - Rated  Current Rating  Silver  Flame Retardant  500VAC, 700VDC  46A	Ingress Protection	Environment Proof
Features Flame Retardant  Voltage - Rated 500VAC, 700VDC  Current Rating 46A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating 46A	Contact Finish	Silver
Current Rating 46A	Features	Flame Retardant
-	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	46A
		Report errors?

#### FRCIR020R-24-10S-F80 Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### FRCIR020R-24-10S-F80 Payment Methods



















# FRCIR020R-24-10S-F80 Shipping Methods













If you have any question about FRCIR020R-24-10S-F80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com