



Heisener.com

FRCIR020R18-19SF80 Information

Part Number FRCIR020R18-19SF80 Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT FMALE 10POS SLVR CRIMP

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FRCIR020R18-19SF80 Specifications

Manufacturer Part Number Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-5015, CIR Connector Type Receptacle, Female Sockets Number of Positions 10 Shell Size - Insert 18-19 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating IREPORT errors?		
Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-5015, CIR Connector Type Receptacle, Female Sockets Number of Positions 10 Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Flame Retardant Voltage - Rated Current Rating 13A	Manufacturer Part Number	FRCIR020R18-19SF80
Circular Connectors Package - Series MIL-DTL-5015, CIR Connector Type Receptacle, Female Sockets Number of Positions 10 Shell Size - Insert 18-19 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Flame Retardant Voltage - Rated Current Rating 13A	Manufacturer	ITT Cannon, LLC
Package - Series MIL-DTL-5015, CIR Connector Type Receptacle, Female Sockets Number of Positions 10 Shell Size - Insert 18-19 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 13A	Category	Connectors, Interconnects
Series MIL-DTL-5015, CIR Connector Type Receptacle, Female Sockets Number of Positions 10 Shell Size - Insert 18-19 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 13A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions10Shell Size - Insert18-19Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating13A	Package	-
Number of Positions Shell Size - Insert 18-19 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 13A	Series	MIL-DTL-5015, CIR
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 13A	Number of Positions	10
Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 13A	Shell Size - Insert	18-19
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 13A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 13A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 13A	Termination	Crimp
Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 13A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Silver Features Flame Retardant Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver Flame Retardant 13A	Orientation	N (Normal)
Contact Finish Silver Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 13A	Ingress Protection	Environment Proof
Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 13A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating 13A	Contact Finish	Silver
Current Rating 13A	Features	Flame Retardant
-	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	13A
		Report errors?

FRCIR020R18-19SF80 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FRCIR020R18-19SF80 Payment Methods



















FRCIR020R18-19SF80 Shipping Methods













If you have any question about FRCIR020R18-19SF80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com