

Heisener.com

FRCIR020R22-19SF80T108

FRCIR020R22-19SF80T108 Information

Part Number FRCIR020R22-19SF80T108

Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 14POS PNL MNT SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FRCIR020R22-19SF80T108 Specifications

Manufacturer Part NumberFRCIR020R22-19SF80T108ManufacturerITT Cannon, LLCCategoryConnectors, Interconnects Circular ConnectorsPackage-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Female SocketsNumber of Positions14Shell Size - Insert22-19Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating13A		
Category Circular Connectors Package - Series MIL-DTL-5015, CIR Connector Type Receptacle, Female Sockets Number of Positions 14 Shell Size - Insert 22-19 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Flame Retardant Voltage - Rated Connectors, Interconnects Circular Connectors HIL-DTL-5015, CIR Receptacle, Female Sockets NIL-DTL-5015, CIR Receptacle, Female Sockets NIL-DTL-5015, CIR Receptacle Sockets NIL-DTL-5015, CIR Receptacle Sockets Number of Positions 14 Shell Mounting Type Panel Mount, Flange Panel Mount	Manufacturer Part Number	FRCIR020R22-19SF80T108
Circular Connectors Package - Series MIL-DTL-5015, CIR Connector Type Receptacle, Female Sockets Number of Positions 14 Shell Size - Insert 22-19 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Flame Retardant Voltage - Rated Contact Fasted Contact Finish Series Connectors MIL-DTL-5015, CIR AUIL-DTL-5015, CIR AUIL-DT	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CIR Connector Type Receptacle, Female Sockets Number of Positions 14 Shell Size - Insert 22-19 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Flame Retardant Voltage - Rated 500VAC, 700VDC	Category	Connectors, Interconnects
Series MIL-DTL-5015, CIR Connector Type Receptacle, Female Sockets Number of Positions 14 Shell Size - Insert 22-19 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Flame Retardant Voltage - Rated 500VAC, 700VDC		Circular Connectors
Connector Type Receptacle, Female Sockets Number of Positions 14 Shell Size - Insert 22-19 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Flame Retardant Voltage - Rated 500VAC, 700VDC	Package	-
Number of Positions Shell Size - Insert 22-19 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Flame Retardant Voltage - Rated 14 22-19 Aunious Aluminum Alloy, Black Zinc Cobalt Plated SouvAC, 700VDC	Series	MIL-DTL-5015, CIR
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Features Flame Retardant Voltage - Rated 22-19 22-19 Auminum State S	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Flame Retardant Voltage - Rated 500VAC, 700VDC	Number of Positions	14
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesFlame RetardantVoltage - Rated500VAC, 700VDC	Shell Size - Insert	22-19
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Flame Retardant Voltage - Rated 500VAC, 700VDC	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Flame Retardant Voltage - Rated S00VAC, 700VDC	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Flame Retardant Voltage - Rated 500VAC, 700VDC	Termination	Crimp
Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Flame Retardant Voltage - Rated 500VAC, 700VDC	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Flame Retardant Voltage - Rated Aluminum Alloy, Black Zinc Cobalt Plated Gold Food Flame Retardant	Orientation	N (Normal)
Contact Finish Gold Features Flame Retardant Voltage - Rated 500VAC, 700VDC	Ingress Protection	Environment Proof
Features Flame Retardant Voltage - Rated 500VAC, 700VDC	Shell Material, Finish	Aluminum Alloy, Black Zinc Cobalt Plated
Voltage - Rated 500VAC, 700VDC	Contact Finish	Gold
	Features	Flame Retardant
Current Rating 13A	Voltage - Rated	500VAC, 700VDC
	Current Rating	13A
Report errors?		Report errors?

FRCIR020R22-19SF80T108 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FRCIR020R22-19SF80T108 Payment Methods

































If you have any question about FRCIR020R22-19SF80T108, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com