

Heisener.com

# FRCIR020R24-20SF80T54

### FRCIR020R24-20SF80T54 Information

Part Number FRCIR020R24-20SF80T54

Manufacturer ITT Cannon, LLC

**Category** Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 11POS PNL MNT SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## FRCIR020R24-20SF80T54 Specifications

Manufacturer Part Number  Manufacturer  Category  Connectors, Interconnects Circular Connectors  Package  - Series  MIL-DTL-5015, CIR  Connector Type  Receptacle, Female Sockets  Number of Positions  11  Shell Size - Insert  Shell Size, MIL  Mounting Type  Panel Mount, Flange  Termination  Crimp  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum, Black Painted  Contact Finish  Features  Flame Retardant  Voltage - Rated  Ouver troos?		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Female SocketsNumber of Positions11Shell Size - Insert24-20Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum, Black PaintedContact FinishSilverFeaturesFlame RetardantVoltage - Rated900VAC, 1250VDCCurrent Rating13A, 23A	Manufacturer Part Number	FRCIR020R24-20SF80T54
Package Series MIL-DTL-5015, CIR Connector Type Receptacle, Female Sockets Number of Positions 11 Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Black Painted Contact Finish Features Features Flame Retardant Voltage - Rated Current Rating MIL-DTL-5015, CIR Receptacle, Female Sockets MIL Crimp Receptacle, Female Sockets Paceptacle, Female Sockets NIL Contact Finish Fund Subject Features Flame Retardant Voltage - Rated Jay 23A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Female SocketsNumber of Positions11Shell Size - Insert24-20Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum, Black PaintedContact FinishSilverFeaturesFlame RetardantVoltage - Rated900VAC, 1250VDCCurrent Rating13A, 23A	Category	Connectors, Interconnects
Series MIL-DTL-5015, CIR Connector Type Receptacle, Female Sockets Number of Positions 11 Shell Size - Insert 24-20 Shell Size, MIL		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions11Shell Size - Insert24-20Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum, Black PaintedContact FinishSilverFeaturesFlame RetardantVoltage - Rated900VAC, 1250VDCCurrent Rating13A, 23A	Package	-
Number of Positions11Shell Size - Insert24-20Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum, Black PaintedContact FinishSilverFeaturesFlame RetardantVoltage - Rated900VAC, 1250VDCCurrent Rating13A, 23A	Series	MIL-DTL-5015, CIR
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum, Black Painted Contact Finish Silver Features Flame Retardant Voltage - Rated Output Description Shell Material Voltage - Rated 13A, 23A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum, Black Painted  Contact Finish Features Flame Retardant Voltage - Rated 900VAC, 1250VDC  Current Rating	Number of Positions	11
Mounting Type Panel Mount, Flange  Termination Crimp  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Proof Shell Material, Finish Aluminum, Black Painted  Contact Finish Silver  Features Flame Retardant  Voltage - Rated 900VAC, 1250VDC  Current Rating 13A, 23A	Shell Size - Insert	24-20
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum, Black Painted Contact Finish Silver Features Flame Retardant Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 23A	Shell Size, MIL	-
Fastening Type  Orientation  N (Normal)  Ingress Protection  Environment Proof  Shell Material, Finish  Aluminum, Black Painted  Contact Finish  Silver  Features  Flame Retardant  Voltage - Rated  900VAC, 1250VDC  Current Rating  13A, 23A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum, Black Painted Contact Finish Silver Features Flame Retardant Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 23A	Termination	Crimp
Ingress Protection  Environment Proof  Aluminum, Black Painted  Contact Finish  Contact Finish  Features  Flame Retardant  Voltage - Rated  900VAC, 1250VDC  Current Rating  13A, 23A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Silver Features Flame Retardant Voltage - Rated Ourrent Rating Aluminum, Black Painted Silver Flame Retardant 13A, 23A	Orientation	N (Normal)
Contact Finish  Features  Flame Retardant  Voltage - Rated  900VAC, 1250VDC  Current Rating  13A, 23A	Ingress Protection	Environment Proof
Features Flame Retardant  Voltage - Rated 900VAC, 1250VDC  Current Rating 13A, 23A	Shell Material, Finish	Aluminum, Black Painted
Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 23A	Contact Finish	Silver
Current Rating 13A, 23A	Features	Flame Retardant
•	Voltage - Rated	900VAC, 1250VDC
Report errors?	Current Rating	13A, 23A
1		Report errors?

#### FRCIR020R24-20SF80T54 Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### FRCIR020R24-20SF80T54 Payment Methods





















### FRCIR020R24-20SF80T54 Shipping Methods













If you have any question about FRCIR020R24-20SF80T54, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com