

Heisener.com

FRCIR02RFS20-15SF80T39

FRCIR02RFS20-15SF80T39 Information

Part Number FRCIR02RFS20-15SF80T39

Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 7POS PNL MNT SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FRCIR02RFS20-15SF80T39 Specifications

Manufacturer Part NumberFRCIR02RFS20-15SF80T39ManufacturerITT Cannon, LLCCategoryConnectors, Interconnects Circular ConnectorsPackage-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert20-15Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum, Black Epoxyurhetanic Varnish PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating23A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert20-15Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum, Black Epoxyurhetanic Varnish PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating23A	Manufacturer Part Number	FRCIR02RFS20-15SF80T39
Package-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert20-15Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum, Black Epoxyurhetanic Varnish PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating23A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert20-15Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum, Black Epoxyurhetanic Varnish PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating23A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert20-15Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum, Black Epoxyurhetanic Varnish PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating23A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert20-15Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum, Black Epoxyurhetanic Varnish PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating23A	Package	-
Number of Positions7Shell Size - Insert20-15Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum, Black Epoxyurhetanic Varnish PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating23A	Series	MIL-DTL-5015, CIR
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum, Black Epoxyurhetanic Varnish Plated Contact Finish Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 23A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum, Black Epoxyurhetanic Varnish Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 23A	Number of Positions	7
Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum, Black Epoxyurhetanic Varnish Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 23A	Shell Size - Insert	20-15
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum, Black Epoxyurhetanic Varnish Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 23A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum, Black Epoxyurhetanic Varnish Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 23A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum, Black Epoxyurhetanic Varnish Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 23A	Termination	Crimp
Ingress Protection Environment Proof Shell Material, Finish Aluminum, Black Epoxyurhetanic Varnish Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 23A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Silver Features Flame Retardant Voltage - Rated Current Rating Aluminum, Black Epoxyurhetanic Varnish Plated Silver Flame Retardant 23A	Orientation	N (Normal)
Contact Finish Silver Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 23A	Ingress Protection	Environment Proof
Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 23A	Shell Material, Finish	Aluminum, Black Epoxyurhetanic Varnish Plated
Voltage - Rated 500VAC, 700VDC Current Rating 23A	Contact Finish	Silver
Current Rating 23A	Features	Flame Retardant
	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	23A
		Report errors?

FRCIR02RFS20-15SF80T39 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FRCIR02RFS20-15SF80T39 Payment Methods



















FRCIR02RFS20-15SF80T39 Shipping Methods













If you have any question about FRCIR02RFS20-15SF80T39, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com