

Heisener.com

# FRCIR030-10SL-4PF80T108

### FRCIR030-10SL-4PF80T108 Information

Part Number FRCIR030-10SL-4PF80T108

Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 2POS PNL MNT PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# FRCIR030-10SL-4PF80T108 Specifications

Manufacturer Part Number     FRCIR030-10SL-4PF80T108       Manufacturer     ITT Cannon, LLC       Category     Connectors, Interconnects       Package     -       Series     MIL-DTL-5015, CIR       Connector Type     Receptacle, Male Pins       Number of Positions     2       Shell Size - Insert     10SL-4       Shell Size, MIL     -       Mounting Type     Panel Mount, Flange       Termination     Crimp       Fastening Type     Bayonet Lock       Orientation     N (Normal)       Ingress Protection     -       Shell Material, Finish     Aluminum Alloy, Black Zinc Cobalt Plated       Contact Finish     Gold       Features     Flame Retardant       Voltage - Rated     500VAC, 700VDC       Current Rating     13A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Male PinsNumber of Positions2Shell Size - Insert10SL-4Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating13A	Manufacturer Part Number	FRCIR030-10SL-4PF80T108
Circular ConnectorsPackage-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Male PinsNumber of Positions2Shell Size - Insert10SL-4Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating13A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Male PinsNumber of Positions2Shell Size - Insert10SL-4Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating13A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Male PinsNumber of Positions2Shell Size - Insert10SL-4Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating13A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions2Shell Size - Insert10SL-4Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating13A	Package	-
Number of Positions2Shell Size - Insert10SL-4Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating13A	Series	MIL-DTL-5015, CIR
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Flame Retardant Voltage - Rated Current Rating 13A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish Features Flame Retardant  Voltage - Rated  Current Rating 13A	Number of Positions	2
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating13A	Shell Size - Insert	10SL-4
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 13A	Shell Size, MIL	-
Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish  Gold  Features  Flame Retardant  Voltage - Rated  500VAC, 700VDC  Current Rating	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 13A	Termination	Crimp
Ingress Protection - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 13A	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Gold  Features  Flame Retardant  Voltage - Rated  Current Rating  Aluminum Alloy, Black Zinc Cobalt Plated  Gold  Flame Retardant  13A	Orientation	N (Normal)
Contact Finish Gold Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 13A	Ingress Protection	-
Features Flame Retardant  Voltage - Rated 500VAC, 700VDC  Current Rating 13A	Shell Material, Finish	Aluminum Alloy, Black Zinc Cobalt Plated
Voltage - Rated 500VAC, 700VDC Current Rating 13A	Contact Finish	Gold
Current Rating 13A	Features	Flame Retardant
	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	13A
		Report errors?

### FRCIR030-10SL-4PF80T108 Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## FRCIR030-10SL-4PF80T108 Payment Methods





















## FRCIR030-10SL-4PF80T108 Shipping Methods













If you have any question about FRCIR030-10SL-4PF80T108, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com