

**FRCIR030-20-4P-F80-T89-12 Information**


For Reference Only

**Part Number** [FRCIR030-20-4P-F80-T89-12](#)  
**Manufacturer** ITT Cannon, LLC  
**Category** Connectors, Interconnects  
[Circular Connectors](#)  
**Description** CONN RCPT 4POS PNL MNT PIN  
**Package** -  
 For the pricing/inventory/lead time, please contact us  
 Website: <https://www.heisener.com>  
 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)



[Request a Quote](#)

**Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.


**FRCIR030-20-4P-F80-T89-12 Specifications**

Manufacturer Part Number	<a href="#">FRCIR030-20-4P-F80-T89-12</a>
Manufacturer	ITT Cannon, LLC
Category	Connectors, Interconnects <a href="#">Circular Connectors</a>
Package	-
Series	MIL-DTL-5015, CIR
Connector Type	Receptacle, Male Pins
Number of Positions	4
Shell Size - Insert	20-4
Shell Size, MIL	-
Mounting Type	Panel Mount, Flange
Termination	Crimp
Fastening Type	Bayonet Lock
Orientation	N (Normal)
Ingress Protection	-
Shell Material, Finish	Aluminum Alloy, Anodized Black Plated
Contact Finish	Silver
Features	Flame Retardant
Voltage - Rated	900VAC, 1250VDC
Current Rating	23A
	<a href="#">Report errors?</a>

## FRCIR030-20-4P-F80-T89-12 Guarantees



### Quality Guarantees

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## FRCIR030-20-4P-F80-T89-12 Payment Methods



## FRCIR030-20-4P-F80-T89-12 Shipping Methods



If you have any question about FRCIR030-20-4P-F80-T89-12, please do not hesitate to contact us!

Website: <https://www.heisener.com>

E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)