

Heisener.com

FRCIR030-22-14PW-F80

FRCIR030-22-14PW-F80 Information

Part Number FRCIR030-22-14PW-F80

Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 19POS PNL MNT PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FRCIR030-22-14PW-F80 Specifications

| Manufacturer Part NumberFRCIR030-22-14PW-F80ManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Male PinsNumber of Positions19Shell Size - Insert22-14Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationWIngress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating13A | | |
|--|--------------------------|---|
| CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Male PinsNumber of Positions19Shell Size - Insert22-14Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationWIngress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating13A | Manufacturer Part Number | FRCIR030-22-14PW-F80 |
| Package-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Male PinsNumber of Positions19Shell Size - Insert22-14Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationWIngress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating13A | Manufacturer | ITT Cannon, LLC |
| Package-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Male PinsNumber of Positions19Shell Size - Insert22-14Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationWIngress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating13A | Category | Connectors, Interconnects |
| SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Male PinsNumber of Positions19Shell Size - Insert22-14Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationWIngress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating13A | | Circular Connectors |
| Connector TypeReceptacle, Male PinsNumber of Positions19Shell Size - Insert22-14Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationWIngress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating13A | Package | - |
| Number of Positions19Shell Size - Insert22-14Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationWIngress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating13A | Series | MIL-DTL-5015, CIR |
| Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation W Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Flame Retardant Voltage - Rated Current Rating 13A | Connector Type | Receptacle, Male Pins |
| Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation W Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 13A | Number of Positions | 19 |
| Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation W Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 13A | Shell Size - Insert | 22-14 |
| Termination Crimp Fastening Type Bayonet Lock Orientation W Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 13A | Shell Size, MIL | - |
| Fastening Type Bayonet Lock Orientation W Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 13A | Mounting Type | Panel Mount, Flange |
| Orientation W Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 13A | Termination | Crimp |
| Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 13A | Fastening Type | Bayonet Lock |
| Shell Material, Finish Contact Finish Silver Features Flame Retardant Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver Flame Retardant 13A | Orientation | W |
| Contact Finish Silver Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 13A | Ingress Protection | - |
| Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 13A | Shell Material, Finish | Aluminum Alloy, Olive Drab Cadmium Plated |
| Voltage - Rated 500VAC, 700VDC Current Rating 13A | Contact Finish | Silver |
| Current Rating 13A | Features | Flame Retardant |
| | Voltage - Rated | 500VAC, 700VDC |
| Report errors? | Current Rating | 13A |
| | | Report errors? |

FRCIR030-22-14PW-F80 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FRCIR030-22-14PW-F80 Payment Methods



















FRCIR030-22-14PW-F80 Shipping Methods













If you have any question about FRCIR030-22-14PW-F80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com