

Heisener.com

# FRCIR030FP28-20SF80T108

### FRCIR030FP28-20SF80T108 Information

Part Number FRCIR030FP28-20SF80T108

Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 14POS PNL MNT SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# FRCIR030FP28-20SF80T108 Specifications

Manufacturer Part Number     FRCIR030FP28-20SF80T108       Manufacturer     ITT Cannon, LLC       Category     Connectors, Interconnects       Package     -       Series     MIL-DTL-5015, CIR       Connector Type     Receptacle, Female Sockets       Number of Positions     14       Shell Size - Insert     28-20       Shell Size, MIL     -       Mounting Type     Panel Mount, Flange       Termination     Crimp       Fastening Type     Bayonet Lock       Orientation     N (Normal)       Ingress Protection     -       Shell Material, Finish     Aluminum Alloy, Black Zinc Cobalt Plated       Contact Finish     Silver       Features     Flame Retardant       Voltage - Rated     500VAC, 700VDC       Current Rating     13A, 23A		
Category Circular Connectors  Package - Series MIL-DTL-5015, CIR Connector Type Receptacle, Female Sockets Number of Positions 14 Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Features Flame Retardant Voltage - Rated Current Rating 1 Cinnel Circular Connectors  MIL-DTL-5015, CIR Receptacle, Female Sockets MIL-DTL-5015, CIR Receptacle, Female Sockets  Null-DTL-5015, CIR Receptacle, Female Sockets  Number of Positions 14 Shell Material, Finish Crimp Bayonet Lock Ni (Normal) Ingress Protection Silver Features Flame Retardant Voltage - Rated S00VAC, 700VDC Current Rating 13A, 23A	Manufacturer Part Number	FRCIR030FP28-20SF80T108
Package-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Female SocketsNumber of Positions14Shell Size - Insert28-20Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating13A, 23A	Manufacturer	ITT Cannon, LLC
Package - Series MIL-DTL-5015, CIR Connector Type Receptacle, Female Sockets Number of Positions 14 Shell Size - Insert 28-20 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 113A, 23A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Female SocketsNumber of Positions14Shell Size - Insert28-20Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating13A, 23A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions14Shell Size - Insert28-20Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated500VAC, 700VDCCurrent Rating13A, 23A	Package	-
Number of Positions  Shell Size - Insert  28-20  Shell Size, MIL  Mounting Type  Panel Mount, Flange  Termination  Crimp  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish  Features  Flame Retardant  Voltage - Rated  500VAC, 700VDC  Current Rating  13A, 23A	Series	MIL-DTL-5015, CIR
Shell Size - Insert 28-20 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 13A, 23A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish Features Flame Retardant  Voltage - Rated 500VAC, 700VDC  Current Rating 13A, 23A	Number of Positions	14
Mounting Type Panel Mount, Flange  Termination Crimp  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish Silver  Features Flame Retardant  Voltage - Rated 500VAC, 700VDC  Current Rating 13A, 23A	Shell Size - Insert	28-20
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 13A, 23A	Shell Size, MIL	-
Fastening Type  Bayonet Lock Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish  Silver  Features  Flame Retardant  Voltage - Rated  500VAC, 700VDC  Current Rating  13A, 23A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 13A, 23A	Termination	Crimp
Ingress Protection - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 500VAC, 700VDC Current Rating 13A, 23A	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Silver  Features  Flame Retardant  Voltage - Rated  Current Rating  Aluminum Alloy, Black Zinc Cobalt Plated  Silver  Flame Retardant  13A, 23A	Orientation	N (Normal)
Contact Finish Silver Features Flame Retardant Voltage - Rated Current Rating 13A, 23A	Ingress Protection	-
Features Flame Retardant  Voltage - Rated 500VAC, 700VDC  Current Rating 13A, 23A	Shell Material, Finish	Aluminum Alloy, Black Zinc Cobalt Plated
Voltage - Rated 500VAC, 700VDC Current Rating 13A, 23A	Contact Finish	Silver
Current Rating 13A, 23A	Features	Flame Retardant
-	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	13A, 23A
		Report errors?

### FRCIR030FP28-20SF80T108 Guarantees



### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## FRCIR030FP28-20SF80T108 Payment Methods





















## FRCIR030FP28-20SF80T108 Shipping Methods













If you have any question about FRCIR030FP28-20SF80T108, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com