

Heisener.com

FRCIR030RV32A-13PF80T108

FRCIR030RV32A-13PF80T108 Information

Part Number FRCIR030RV32A-13PF80T108

Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 13POS PNL MNT PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FRCIR030RV32A-13PF80T108 Specifications

Manufacturer Part Number FRCIR030RV32A-13PF80T108 Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series MIL-DTL-5015, CIR Connector Type Receptacle, Male Pins Number of Positions 13 Shell Size - Insert 32-A13 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 900VAC, 1250VDC Current Rating 23A		
Category Circular Connectors Package - Series MIL-DTL-5015, CIR Connector Type Receptacle, Male Pins Number of Positions 13 Shell Size - Insert 32-A13 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Features Flame Retardant Voltage - Rated Current Rating 2- Circular Connectors MIL-DTL-5015, CIR Receptacle, Male Pins MIL-DTL-5015, CIR Receptacle, Male Pins Netherous Bayonet Lock Crimp Bayonet Lock N (Normal) Silver Flame Retardant Voltage - Rated 900VAC, 1250VDC Current Rating	Manufacturer Part Number	FRCIR030RV32A-13PF80T108
Package-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Male PinsNumber of Positions13Shell Size - Insert32-A13Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated900VAC, 1250VDCCurrent Rating23A	Manufacturer	ITT Cannon, LLC
Package - Series MIL-DTL-5015, CIR Connector Type Receptacle, Male Pins Number of Positions 13 Shell Size - Insert 32-A13 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 900VAC, 1250VDC Current Rating 223A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Male PinsNumber of Positions13Shell Size - Insert32-A13Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated900VAC, 1250VDCCurrent Rating23A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions13Shell Size - Insert32-A13Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated900VAC, 1250VDCCurrent Rating23A	Package	-
Number of Positions Shell Size - Insert 32-A13 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Features Flame Retardant Voltage - Rated 900VAC, 1250VDC Current Rating 23A	Series	MIL-DTL-5015, CIR
Shell Size - Insert 32-A13 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 900VAC, 1250VDC Current Rating 23A	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Features Flame Retardant Voltage - Rated 900VAC, 1250VDC Current Rating 23A	Number of Positions	13
Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 900VAC, 1250VDC Current Rating 23A	Shell Size - Insert	32-A13
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 900VAC, 1250VDC Current Rating 23A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 900VAC, 1250VDC Current Rating 23A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 900VAC, 1250VDC Current Rating 23A	Termination	Crimp
Ingress Protection Environment Proof Shell Material, Finish Contact Finish Silver Features Flame Retardant Voltage - Rated 900VAC, 1250VDC Current Rating Environment Proof Aluminum Alloy, Black Zinc Cobalt Plated Silver Flame Retardant 23A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Silver Features Flame Retardant Voltage - Rated Ourrent Rating Aluminum Alloy, Black Zinc Cobalt Plated Silver Flame Retardant 23A	Orientation	N (Normal)
Contact Finish Silver Features Flame Retardant Voltage - Rated 900VAC, 1250VDC Current Rating 23A	Ingress Protection	Environment Proof
Features Flame Retardant Voltage - Rated 900VAC, 1250VDC Current Rating 23A	Shell Material, Finish	Aluminum Alloy, Black Zinc Cobalt Plated
Voltage - Rated 900VAC, 1250VDC Current Rating 23A	Contact Finish	Silver
Current Rating 23A	Features	Flame Retardant
	Voltage - Rated	900VAC, 1250VDC
Report errors?	Current Rating	23A
		Report errors?

FRCIR030RV32A-13PF80T108 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FRCIR030RV32A-13PF80T108 Payment Methods



















FRCIR030RV32A-13PF80T108 Shipping Methods













If you have any question about FRCIR030RV32A-13PF80T108, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com