

Heisener.com

# FRCIR26-20-4PF80T108-D204

### FRCIR26-20-4PF80T108-D204 Information

Part Number FRCIR26-20-4PF80T108-D204

Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 4POS PNL MNT PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## FRCIR26-20-4PF80T108-D204 Specifications

Manufacturer Part Number     FRCIR26-20-4PF80T108-D204       Manufacturer     ITT Cannon, LLC       Category     Connectors, Interconnects       Package     -       Series     MIL-DTL-5015, CIR       Connector Type     Plug, Male Pins       Number of Positions     4       Shell Size - Insert     20-4       Shell Size, MIL     -       Mounting Type     Panel Mount       Termination     Crimp       Fastening Type     Bayonet Lock       Orientation     N (Normal)       Ingress Protection     -       Shell Material, Finish     Aluminum Alloy, Black Zinc Cobalt Plated       Contact Finish     Silver       Features     Flame Retardant       Voltage - Rated     900VAC, 1250VDC       Current Rating     23A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CIRConnector TypePlug, Male PinsNumber of Positions4Shell Size - Insert20-4Shell Size, MIL-Mounting TypePanel MountTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated900VAC, 1250VDCCurrent Rating23A	Manufacturer Part Number	FRCIR26-20-4PF80T108-D204
Package-SeriesMIL-DTL-5015, CIRConnector TypePlug, Male PinsNumber of Positions4Shell Size - Insert20-4Shell Size, MIL-Mounting TypePanel MountTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated900VAC, 1250VDCCurrent Rating23A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CIRConnector TypePlug, Male PinsNumber of Positions4Shell Size - Insert20-4Shell Size, MIL-Mounting TypePanel MountTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated900VAC, 1250VDCCurrent Rating23A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CIRConnector TypePlug, Male PinsNumber of Positions4Shell Size - Insert20-4Shell Size, MIL-Mounting TypePanel MountTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated900VAC, 1250VDCCurrent Rating23A		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions4Shell Size - Insert20-4Shell Size, MIL-Mounting TypePanel MountTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishSilverFeaturesFlame RetardantVoltage - Rated900VAC, 1250VDCCurrent Rating23A	Package	-
Number of Positions  Shell Size - Insert  20-4  Shell Size, MIL  Mounting Type  Panel Mount  Termination  Crimp  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish  Features  Flame Retardant  Voltage - Rated  900VAC, 1250VDC  Current Rating  23A	Series	MIL-DTL-5015, CIR
Shell Size - Insert 20-4 Shell Size, MIL - Mounting Type Panel Mount Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 900VAC, 1250VDC Current Rating 23A	Connector Type	Plug, Male Pins
Shell Size, MIL  Mounting Type Panel Mount  Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish Features Flame Retardant  Voltage - Rated 900VAC, 1250VDC  Current Rating 23A	Number of Positions	4
Mounting Type Panel Mount  Termination Crimp  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish Silver  Features Flame Retardant  Voltage - Rated 900VAC, 1250VDC  Current Rating 23A	Shell Size - Insert	20-4
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 900VAC, 1250VDC Current Rating 23A	Shell Size, MIL	-
Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish  Silver  Features  Flame Retardant  Voltage - Rated  900VAC, 1250VDC  Current Rating  23A	Mounting Type	Panel Mount
Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 900VAC, 1250VDC Current Rating 23A	Termination	Crimp
Ingress Protection - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features Flame Retardant Voltage - Rated 900VAC, 1250VDC Current Rating 23A	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Silver  Features  Flame Retardant  Voltage - Rated  Ourrent Rating  Aluminum Alloy, Black Zinc Cobalt Plated  Silver  Flame Retardant  23A	Orientation	N (Normal)
Contact Finish Silver Features Flame Retardant Voltage - Rated 900VAC, 1250VDC Current Rating 23A	Ingress Protection	-
Features Flame Retardant  Voltage - Rated 900VAC, 1250VDC  Current Rating 23A	Shell Material, Finish	Aluminum Alloy, Black Zinc Cobalt Plated
Voltage - Rated 900VAC, 1250VDC Current Rating 23A	Contact Finish	Silver
Current Rating 23A	Features	Flame Retardant
	Voltage - Rated	900VAC, 1250VDC
Report errors?	Current Rating	23A
		Report errors?

#### FRCIR26-20-4PF80T108-D204 Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### FRCIR26-20-4PF80T108-D204 Payment Methods





















## FRCIR26-20-4PF80T108-D204 Shipping Methods













If you have any question about FRCIR26-20-4PF80T108-D204, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com