

FRN-R-25 Information

Heisener.com

Part Number FRN-R-25
Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE TRON DUAL-ELEMENT CLASS RK5

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FRN-R-25 Specifications

Manufacturer Part NumberFRN-R-25ManufacturerEatonCategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesFusetron? FRN-RFuse TypeCartridgeCurrent Rating25AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 2.00" L (14.22mm x 50.80mm)Report errors?		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesFusetron? FRN-RFuse TypeCartridgeCurrent Rating25AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Manufacturer Part Number	FRN-R-25
PackageCartridge, Non-StandardSeriesFusetron? FRN-RFuse TypeCartridgeCurrent Rating25AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Manufacturer	Eaton
PackageCartridge, Non-StandardSeriesFusetron? FRN-RFuse TypeCartridgeCurrent Rating25AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Category	Circuit Protection
SeriesFusetron? FRN-RFuse TypeCartridgeCurrent Rating25AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 2.00" L (14.22mm x 50.80mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 25A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cartridge 25A 250V Eatridge Electrical, Industrial Clectrical, Industrial Features - Class RK5 ARK5 AC, CE, CSA, UL CE, CSA, UL COPERATION CONTROL CONTR	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 25A 25A 25D 25D 25D 25D 25D 25D	Series	Fusetron? FRN-R
Voltage Rating - AC Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 250V 125V	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 125V Response Time Slow Clex CSA RK5 RK5 Approvals CE, CSA, UL CE, CSA, UL COPRATION COPPARITMENT COP	Current Rating	25A
Response Time Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Slow Approvals - Cartridge, Non-Standard 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Voltage Rating - AC	250V
Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Voltage Rating - DC	125V
Features - Class RK5 Approvals CE, CSA, UL Operating Temperature - Streaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Response Time	Slow
Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension O.560" Dia x 2.00" L (14.22mm x 50.80mm)	Class	RK5
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.560" Dia x 2.00" L (14.22mm x 50.80mm)
		Report errors?

FRN-R-25 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FRN-R-25 Payment Methods





















FRN-R-25 Shipping Methods













If you have any question about FRN-R-25, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com