

FRN-R-3-2/10 Information

Heisener.com

Part Number FRN-R-3-2/10

Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE TRON DUAL-ELEMENT CLASS RK5

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FRN-R-3-2/10 Specifications

Manufacturer Part Number Manufacturer Eaton Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series Fuse Type Cartridge Current Rating 3.2A Voltage Rating - AC Voltage Rating - DC Response Time Applications Features Class Approvals Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Eaton Circuit Protection Eaton Circuit Protection Electrical, Specialty Fuses Cartridge, Non-Standard Fusetron? FRN-R Cartridge 2atridge Cartridge Solv Cartridge Solv Lettrical, Industrial Electrical, Industrial CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC		
Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series Fusetron? FRN-R Fuse Type Cartridge Current Rating 3.2A Voltage Rating - AC Voltage Rating - DC Response Time Applications Electrical, Industrial Features - Class RK5 Approvals Operating Temperature - Circuit Protection Electrical, Specialty Fuses Fusetron? FRN-R Cartridge Cartridge Cartridge Cartridge Cartridge Solv Solv Apslow Apslow RK5 CE, CSA, UL Operating Temperature	Manufacturer Part Number	FRN-R-3-2/10
Electrical, Specialty Fuses Package Cartridge, Non-Standard Series Fusetron? FRN-R Fuse Type Cartridge Current Rating 3.2A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals Operating Temperature -	Manufacturer	Eaton
Package Cartridge, Non-Standard Series Fusetron? FRN-R Fuse Type Cartridge Current Rating 3.2A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature -	Category	Circuit Protection
Series Fusetron? FRN-R Fuse Type Cartridge Current Rating 3.2A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature -		Electrical, Specialty Fuses
Fuse Type Cartridge Current Rating 3.2A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature -	Package	Cartridge, Non-Standard
Current Rating 3.2A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature -	Series	Fusetron? FRN-R
Voltage Rating - AC Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals Operating Temperature - 250V 125V Response Time Slow RK5 CLass RK5 Approvals CE, CSA, UL -	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature	Current Rating	3.2A
Response Time Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature -	Voltage Rating - AC	250V
Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature -	Voltage Rating - DC	125V
Features - Class RK5 Approvals CE, CSA, UL Operating Temperature -	Response Time	Slow
Class RK5 Approvals CE, CSA, UL Operating Temperature -	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature -	Features	-
Operating Temperature -	Class	RK5
	Approvals	CE, CSA, UL
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC	Operating Temperature	-
	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Mounting Type Holder	Mounting Type	Holder
Package / Case Cartridge, Non-Standard	Package / Case	Cartridge, Non-Standard
Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Size / Dimension	0.560" Dia x 2.00" L (14.22mm x 50.80mm)
Report errors?		Report errors?

FRN-R-3-2/10 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FRN-R-3-2/10 Payment Methods





















FRN-R-3-2/10 Shipping Methods













If you have any question about FRN-R-3-2/10, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com