

FRN-R-5-6/10 Information

Heisener.com

Part Number FRN-R-5-6/10

Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE TRON DUAL-ELEMENT CLASS RK5

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FRN-R-5-6/10 Specifications

Manufacturer Part NumberFRN-R-5-6/10ManufacturerEatonCategoryCircuit ProtectionBeackageCartridge, Non-StandardSeriesFusetron? FRN-RFuse TypeCartridgeCurrent Rating5.6AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 2.00" L (14.22mm x 50.80mm)Report errors?		
Category Circuit Protection Electrical, Specialty Fuses Cartridge, Non-Standard Series Fusetron? FRN-R Fuse Type Cartridge Current Rating 5.6A Voltage Rating - AC Voltage Rating - DC Response Time Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cartridge, Non-Standard Electrical, Industrial Circuit Protection Electrical, Industrial CE, CSA, UL Operating Temperature - Class Cartridge, Non-Standard Size / Dimension Circuit Protection Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension Circuit Protection Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension Circuit Protection Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension Circuit Protection Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension Circuit Protection Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension Circuit Protection Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension Circuit Protection Electrical, Industrial Size / Dimension Cartridge, Non-Standard Circuit Protection Cartridge, Non-Standard Cartridge, Non-Standard Circuit Protection Cartridge Cartridge Circuit Protection Cartridge Cartridge Cartridge Circuit Protection Cartridge Cartridge Circuit Protection Cartridge Cartridge Cartridge Cartridge Circuit Protection Cartridge Cartridge Cartrid	Manufacturer Part Number	FRN-R-5-6/10
Beckage Cartridge, Non-Standard Fuser Type Cartridge Current Rating 5.6A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage CC, Cartridge CONA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Cartridge, Non-Standard Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Cartr	Manufacturer	Eaton
PackageCartridge, Non-StandardSeriesFusetron? FRN-RFuse TypeCartridgeCurrent Rating5.6AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Category	Circuit Protection
Fuse Type Cartridge Current Rating 5.6A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Cartridge, Non-Standard Cartridge, Non-Standard Octor Cartridge, Non-Standard Cartridge, Non-Standard Octor Cartridge, Non-Standard		Electrical, Specialty Fuses
Fuse Type Current Rating 5.6A Voltage Rating - AC Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cartridge S50V RESPONSE SION SION SION SION SION SION SION SION	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 5.6A 250V CE, CSA CE, CSA CE, CSA CE, CSA CE, CSA, UL COPIE HOLDE Cartridge, Non-Standard Size / Dimension 5.66 Cartridge, Non-Standard Size / Dimension 5.67 Size / Dimension 5.68 Cartridge, Non-Standard Size / Dimension 5.68 Cartridge, Non-Standard Cartridge, Non-Standard Size / Dimension	Series	Fusetron? FRN-R
Voltage Rating - AC Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 250V 125V 125V 125V 125V 125V 125V 125V 125V 126V 1270 128V	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 125V 125	Current Rating	5.6A
Response Time Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Slow Slow Slow Slow Electrical, Industrial - CE, CSA, UL CE, CSA, UL - Cartridge, Non-Standard 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Voltage Rating - AC	250V
Applications Electrical, Industrial Features Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Electrical, Industrial Electrical Industrial Electrical Industrial Electrical Industrial Electrical Industrial El	Voltage Rating - DC	125V
Features - Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Response Time	Slow
Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension O.560" Dia x 2.00" L (14.22mm x 50.80mm)	Class	RK5
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.560" Dia x 2.00" L (14.22mm x 50.80mm)
		Report errors?

FRN-R-5-6/10 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FRN-R-5-6/10 Payment Methods





















FRN-R-5-6/10 Shipping Methods













If you have any question about FRN-R-5-6/10, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com