

FRN-R-8/10 Information

Heisener.com

Part Number FRN-R-8/10

Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE TRON DUAL-ELEMENT CLASS RK5

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FRN-R-8/10 Specifications

Manufacturer Part Number Manufacturer Eaton Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series Fuse Type Cartridge Current Rating Voltage Rating - AC Voltage Rating - DC Response Time Applications Features Class Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Package / Case Cartridge, Non-Standard Slow CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Package / Case Cartridge, Non-Standard O.560" Dia x 2.00" L (14.22mm x 50.80mm)		
Category Circuit Protection Electrical, Specialty Fuses Cartridge, Non-Standard Series Fusetron? FRN-R Fuse Type Cartridge Current Rating 8mA Voltage Rating - AC Voltage Rating - DC Response Time Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cartridge, Non-Standard Electrical, Industrial Features - Cartridge Circuit Protection Electrical, Specialty Fuses Fusetron? FRN-R Fusetron? Fusetron? Fusetron?	Manufacturer Part Number	FRN-R-8/10
Electrical, Specialty Fuses Package Cartridge, Non-Standard Series Fuse Type Cartridge Current Rating 8mA Voltage Rating - AC Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension Electrical, Industrial CE, CSA, UL CE, CSA, UL CE, CSA, UL CE, CSA, UL COPERATION CONTROL CONTRO	Manufacturer	Eaton
Package Cartridge, Non-Standard Series Fusetron? FRN-R Fuse Type Cartridge Current Rating 8mA Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Fusetron? FRN-R Eusetron? Fusetron. Eusetron.	Category	Circuit Protection
Fuse Type Cartridge Current Rating 8mA Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Voltage SmA		Electrical, Specialty Fuses
Fuse Type Current Rating 8mA Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cartridge Siov RMA Cartridge Siov Cartridge Cartridge Cartridge Siov Cartridge Siov Cartridge Siov Cartridge Siov Cartridge Cartri	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 8mA 8mA 250V 250V 250V CE, CSA CE, CSA LO CE, CSA CE, CSA CE, CSA, UL COPrating Temperature Cartridge, Non-Standard Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Series	Fusetron? FRN-R
Voltage Rating - AC Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 250V 250V 250V 260V	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 125V Response Time Slow Ce, CSA, UL - RK5 AR5 AR5 CE, CSA, UL - Cartridge, Non-Standard 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Current Rating	8mA
Response Time Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Slow Electrical, Industrial - CE, CSA, UL - CE, CSA, U	Voltage Rating - AC	250V
Applications Features - Class RK5 Approvals Ce, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Electrical, Industrial - RK5 AK5 RK5 AR5 CE, CSA, UL - CE, CSA, UL -	Voltage Rating - DC	125V
Features - Class RK5 Approvals CE, CSA, UL Operating Temperature - Country @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Response Time	Slow
Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension CE, CSA, UL - CARTRIDATE CONTROL OF CONTRO	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension O.560" Dia x 2.00" L (14.22mm x 50.80mm)	Class	RK5
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.560" Dia x 2.00" L (14.22mm x 50.80mm)
Report crisis:		Report errors?

FRN-R-8/10 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FRN-R-8/10 Payment Methods





















FRN-R-8/10 Shipping Methods













If you have any question about FRN-R-8/10, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com