

FRS-R-45ID Information

Heisener.com

Part Number FRS-R-45ID

Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE TRON DUAL ELEMENT FUSE CLAS

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FRS-R-45ID Specifications

Manufacturer Part NumberFRS-R-45IDManufacturerEatonCategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesFusetron? FRS-RFuse TypeCartridgeCurrent Rating45AVoltage Rating - AC600VVoltage Rating - DC250VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.060" Dia x 5.50" L (26.92mm x 139.70mm)Report errors?		
Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series Fusetron? FRS-R Fuse Type Cartridge Current Rating 45A Voltage Rating - AC 600V Voltage Rating - DC 250V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Circuit Protection Electrical, Specialty Fuses Electrical, Industrial Features Indicating CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Holder Cartridge, Non-Standard Size / Dimension	Manufacturer Part Number	FRS-R-45ID
Electrical, Specialty Fuses Package Cartridge, Non-Standard Series Fusetron? FRS-R Fuse Type Cartridge Current Rating 45A Voltage Rating - AC 600V Voltage Rating - DC 250V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Electrical, Specialty Fuses Fusetron? Fusetron? FRS-R Fusetron? Fusetron? Fusetron? Fusetron? Fusetron. Fusetron? Fusetron? Fusetron. Fusetron? Fusetron? Fusetron. Fusetron? Fusetron? Fusetron. Fusetron	Manufacturer	Eaton
Package Cartridge, Non-Standard Series Fusetron? FRS-R Fuse Type Cartridge Current Rating 45A Voltage Rating - AC 600V Voltage Rating - DC 250V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.060" Dia x 5.50" L (26.92mm x 139.70mm)	Category	Circuit Protection
Fuse Type Current Rating 45A Voltage Rating - AC Voltage Rating - DC Response Time Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Fuser Tinge Cartridge (Sartridge Non-Standard) Size / Dimension Cartridge (Cartridge Non-Standard) Cartridge (Sartridge Non-Standard) Cartridge (Sartridge Non-Standard) Cartridge (Sartridge Non-Standard) Size / Dimension Cartridge (Cartridge Non-Standard) Size / Dimension Cartridge (Cartridge Non-Standard) Size / Dimension Cartridge (Sartridge Non-Standard) Size / Dimension Cartridge (Cartridge Non-Standard) Size / Dimension		Electrical, Specialty Fuses
Fuse Type Current Rating 45A Voltage Rating - AC 600V Voltage Rating - DC 250V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Cartridge Cartridge Cartridge, Non-Standard Size / Dimension Cartridge Cartridge, Non-Standard Size / Dimension Conversed Cartridge, Non-Standard Size / Dimension Conversed Cartridge, Non-Standard Size / Dimension	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 250V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 45A 600V 600V 600V 600V 600V 600V 600V 600	Series	Fusetron? FRS-R
Voltage Rating - AC Voltage Rating - DC 250V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 250V 600V 60	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 250V 250V 250V 260V	Current Rating	45A
Response Time Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Slow Slow Slow Slow Slow Slow Slow Electrical, Industrial Electrical, Industrial AR5 RK5 APF RK5 APF APF APF CE, CSA, UL	Voltage Rating - AC	600V
Applications Electrical, Industrial Features Indicating RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Electrical, Industrial Electrical, Industrial RK5 CE, CSA RK5	Voltage Rating - DC	250V
Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.060" Dia x 5.50" L (26.92mm x 139.70mm)	Response Time	Slow
Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.060" Dia x 5.50" L (26.92mm x 139.70mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension CE, CSA, UL - CONTROL OF CONTR	Features	Indicating
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.060" Dia x 5.50" L (26.92mm x 139.70mm)	Class	RK5
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.060" Dia x 5.50" L (26.92mm x 139.70mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.060" Dia x 5.50" L (26.92mm x 139.70mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 1.060" Dia x 5.50" L (26.92mm x 139.70mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 1.060" Dia x 5.50" L (26.92mm x 139.70mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	1.060" Dia x 5.50" L (26.92mm x 139.70mm)
		Report errors?

FRS-R-45ID Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FRS-R-45ID Payment Methods



















FRS-R-45ID Shipping Methods













If you have any question about FRS-R-45ID, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com