

### **FRS-R-50ID Information**

Heisener.com

Part Number FRS-R-50ID

Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE TRON DUAL ELEMENT FUSE CLAS

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **FRS-R-50ID Specifications**

Manufacturer Part NumberFRS-R-50IDManufacturerEatonCategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesFusetron? FRS-RFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC600VVoltage Rating - DC250VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.060" Dia x 5.50" L (26.92mm x 139.70mm)Report errors?		
CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesFusetron? FRS-RFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC600VVoltage Rating - DC250VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.060" Dia x 5.50" L (26.92mm x 139.70mm)	Manufacturer Part Number	FRS-R-50ID
Electrical, Specialty Fuses  Package Cartridge, Non-Standard Series Fusetron? FRS-R  Fuse Type Cartridge Current Rating SoA  Voltage Rating - AC Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  Electrical, Specialty Fuses Electron? FRS-R Fusetron? FRS-R Fuse	Manufacturer	Eaton
PackageCartridge, Non-StandardSeriesFusetron? FRS-RFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC600VVoltage Rating - DC250VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.060" Dia x 5.50" L (26.92mm x 139.70mm)	Category	Circuit Protection
SeriesFusetron? FRS-RFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC600VVoltage Rating - DC250VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.060" Dia x 5.50" L (26.92mm x 139.70mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating50AVoltage Rating - AC600VVoltage Rating - DC250VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.060" Dia x 5.50" L (26.92mm x 139.70mm)	Package	Cartridge, Non-Standard
Current Rating  Voltage Rating - AC  600V  Voltage Rating - DC  250V  Response Time  Slow  Applications  Electrical, Industrial  Features  Indicating  Class  RK5  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  500V  250V  Response Time  Slow  Clectrical, Industrial  Electrical, Industrial  Electrical, Industrial  CE, CSA, UL  CE, CSA, UL  CE, CSA, UL  CE, CSA, UL  100Package / Case  Cartridge, Non-Standard  1000" Dia x 5.50" L (26.92mm x 139.70mm)	Series	Fusetron? FRS-R
Voltage Rating - AC  Voltage Rating - DC  250V  Response Time  Slow  Applications  Electrical, Industrial  Features  Indicating  Class  RK5  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  600V  60	Fuse Type	Cartridge
Voltage Rating - DC  Response Time  Slow  Applications  Electrical, Industrial  Features  Indicating  RK5  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  250V  Response Time  Slow  Clectrical, Industrial  Electrical, Industrial  Electrical, Industrial  CE, CSA, UL  Other  RK5  Approvals  CE, CSA, UL  C	Current Rating	50A
Response Time  Applications  Electrical, Industrial  Features  Indicating  Class  RK5  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  Slow  Slow  Slow  Slow  Slow  Slow  Slow  Slow  Electrical, Industrial  Indicating  RK5  RK5  APPROVALE  CE, CSA, UL	Voltage Rating - AC	600V
Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.060" Dia x 5.50" L (26.92mm x 139.70mm)	Voltage Rating - DC	250V
Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature	Response Time	Slow
Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.060" Dia x 5.50" L (26.92mm x 139.70mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.060" Dia x 5.50" L (26.92mm x 139.70mm)	Features	Indicating
Operating Temperature  Breaking Capacity @ Rated Voltage  200kA AC, 20kA DC  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  1.060" Dia x 5.50" L (26.92mm x 139.70mm)	Class	RK5
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 1.060" Dia x 5.50" L (26.92mm x 139.70mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.060" Dia x 5.50" L (26.92mm x 139.70mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 1.060" Dia x 5.50" L (26.92mm x 139.70mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 1.060" Dia x 5.50" L (26.92mm x 139.70mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	1.060" Dia x 5.50" L (26.92mm x 139.70mm)
		Report errors?

#### FRS-R-50ID Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **FRS-R-50ID Payment Methods**



















### **FRS-R-50ID Shipping Methods**













If you have any question about FRS-R-50ID, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com