

FRS-R-8/10 Information

Heisener.com

Part Number FRS-R-8/10
Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE TRON DUAL ELEMENT FUSE CLAS

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FRS-R-8/10 Specifications

Manufacturer Part Number Eaton Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series Fuse Type Cartridge Current Rating Voltage Rating - AC Voltage Rating - DC Response Time Applications Electrical, Industrial Features Class RK5 Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Package / Case Size / Dimension Eaton Circuit Protection Electrical, Specialty Fuses Cartridge, Non-Standard Ostion Electrical, Industrial Features CE, CSA, UL Operating Temperature Holder Cartridge, Non-Standard Ostion Standard Ostion Standard Ostion Standard Ostion Standard Size / Dimension		
Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series Fusetron? FRS-R Fuse Type Cartridge Current Rating 8mA Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Circuit Protection Electrical, Specialty Fuses Electridge, Non-Standard Size / Dimension Circuit Protection Electrical, Specialty Fuses Electridge, Non-Standard Size / Dimension Circuit Protection Electridge, Non-Standard Size / Dimension	Manufacturer Part Number	FRS-R-8/10
Electrical, Specialty Fuses Package Cartridge, Non-Standard Series Fuse Type Cartridge Current Rating 8mA Voltage Rating - AC Voltage Rating - DC 8esponse Time Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Sinon-Standard Size / Dimension Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension Electrical, Industrial CE, CSA, UL CE, CSA, UL CE, CSA, UL CE, CSA, UL COPERATION OF STANDARD CARTRIDADOR OF STANDARD CARTRIDADOR OF STANDARD STANDARD CARTRIDADOR OF STAND	Manufacturer	Eaton
PackageCartridge, Non-StandardSeriesFusetron? FRS-RFuse TypeCartridgeCurrent Rating8mAVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Category	Circuit Protection
SeriesFusetron? FRS-RFuse TypeCartridgeCurrent Rating8mAVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 8mA Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cartridge 600V Response Slow Response Slow CE, CSA, UL CE, CSA, UL CE, CSA, UL COPERATION CONTRACTOR CONTRACT	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 8mA 8mA 8mA 8mA 600V	Series	Fusetron? FRS-R
Voltage Rating - AC Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 300V 600V	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Slow Slow CE, CSA, UL CE, CSA, UL COPRATION OF TABLE OF THE O	Current Rating	8mA
Response Time Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Slow Electrical, Industrial - CE, CSA, UL - CE, CSA, U	Voltage Rating - AC	600V
Applications Features - Class RK5 Approvals Ce, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Electrical, Industrial - C CACA RK5 RK5 AR5 APFOVAL CE, CSA, UL - CE, CSA, UL C	Voltage Rating - DC	300V
Features - Class RK5 Approvals CE, CSA, UL Operating Temperature - Ereaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Response Time	Slow
Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension CE, CSA, UL CRACK OF CSA, UL CRACK OF CSA, UL CARTRIDGE OF CSA, UL COSA, UL C	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension O.810" Dia x 3.00" L (20.57mm x 76.20mm)	Class	RK5
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Donort amous?	Size / Dimension	0.810" Dia x 3.00" L (20.57mm x 76.20mm)
Report errors?		Report errors?

FRS-R-8/10 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FRS-R-8/10 Payment Methods



















FRS-R-8/10 Shipping Methods













If you have any question about FRS-R-8/10, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com