

### FS16-400-C2-B Information



For Reference Only

Part Number FS16-400-C2-B
Manufacturer Triad Magnetics
Category Transformers
Power Transformers

**Description** XFRMR LAMINATED 6VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# FS16-400-C2-B Specifications

Manufacturer Part Number         FS16-400-C2-B           Manufacturer         Triad Magnetics           Category         Transformers           Package         -           Series         Split Pack?, Class 2/3, FS           Type         Laminated Core           Voltage - Primary         115V, 230V           Voltage - Secondary (Full Load)         Parallel 8V, Series 16V           Current - Output (Max)         Parallel 800mA, Series 400mA           Primary Winding(s)         Dual           Secondary Winding(s)         Dual           Center Tap         No           Power - Max         6 VA           Mounting Type         Through Hole           Termination Style         PC Pin           Size / Dimension         41.28mm L x 33.32mm W           Voltage - Isolation         4200Vrms		
Category         Transformers           Power Transformers           Package         -           Series         Split Pack?, Class 2/3, FS           Type         Laminated Core           Voltage - Primary         115V, 230V           Voltage - Secondary (Full Load)         Parallel 8V, Series 16V           Current - Output (Max)         Parallel 800mA, Series 400mA           Primary Winding(s)         Dual           Secondary Winding(s)         Dual           Center Tap         No           Power - Max         6 VA           Mounting Type         Through Hole           Termination Style         PC Pin           Size / Dimension         41.28mm L x 33.32mm W           Height - Seated (Max)         33.32mm           Voltage - Isolation         4200Vrms	Manufacturer Part Number	FS16-400-C2-B
Package Power Transformers  Package Series Split Pack?, Class 2/3, FS  Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 8V, Series 16V Current - Output (Max) Parallel 800mA, Series 400mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style Size / Dimension 41.28mm L x 33.32mm Voltage - Isolation 4200Vrms	Manufacturer	Triad Magnetics
Package - Series Split Pack?, Class 2/3, FS Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 8V, Series 16V Current - Output (Max) Parallel 800mA, Series 400mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Voltage - Isolation 4200Vrms	Category	Transformers
Series Split Pack?, Class 2/3, FS Type Laminated Core  Voltage - Primary 115V, 230V  Voltage - Secondary (Full Load) Parallel 8V, Series 16V  Current - Output (Max) Parallel 800mA, Series 400mA  Primary Winding(s) Dual  Secondary Winding(s) Dual  Center Tap No  Power - Max 6 VA  Mounting Type Through Hole  Termination Style PC Pin  Size / Dimension 41.28mm L x 33.32mm W  Height - Seated (Max) 33.32mm  Voltage - Isolation 4200Vrms		Power Transformers
Type Laminated Core  Voltage - Primary 115V, 230V  Voltage - Secondary (Full Load) Parallel 8V, Series 16V  Current - Output (Max) Parallel 800mA, Series 400mA  Primary Winding(s) Dual  Secondary Winding(s) Dual  Center Tap No  Power - Max 6 VA  Mounting Type Through Hole  Termination Style PC Pin  Size / Dimension 41.28mm L x 33.32mm W  Voltage - Isolation 4200Vrms	Package	-
Voltage - Primary  Voltage - Secondary (Full Load)  Parallel 8V, Series 16V  Current - Output (Max)  Parallel 800mA, Series 400mA  Primary Winding(s)  Dual  Secondary Winding(s)  Center Tap  No  Power - Max  6 VA  Mounting Type  Through Hole  Termination Style  Size / Dimension  41.28mm L x 33.32mm W  Voltage - Isolation  115V, 230V  Parallel 8V, Series 16V  Parallel 8V, Series 400mA  Parallel 8V, Series 400mA  Parallel 8V, Series 16V  Parallel 8voma, Series 400mA  Primary Winding(s)  Dual  Secondary Winding(s)  Dual  Secondary Winding(s)  Pour Secondary Winding(s)  All 18	Series	Split Pack?, Class 2/3, FS
Voltage - Secondary (Full Load)  Current - Output (Max)  Parallel 8V, Series 16V  Parallel 800mA, Series 400mA  Primary Winding(s)  Dual  Secondary Winding(s)  Center Tap  No  Power - Max  6 V A  Mounting Type  Through Hole  Termination Style  PC Pin  Size / Dimension  41.28mm L x 33.32mm W  Voltage - Isolation  Parallel 8V, Series 16V  Parallel 8V, Series 400mA  Pual  Parallel 8V, Series 16V  Parallel 8V, Series 400mA  Pual  Secondary Winding(s)  Dual  Secondary Winding(s)	Туре	Laminated Core
Current - Output (Max)  Primary Winding(s)  Dual  Secondary Winding(s)  Dual  Center Tap  No  Power - Max  6 VA  Mounting Type  Through Hole  Termination Style  PC Pin  Size / Dimension  41.28mm L x 33.32mm  Voltage - Isolation  Parallel 800mA, Series 400mA  Dual  August Pual  Pual  August Pual  August Pual  August Parallel 800mA, Series 400mA  Pual  Pual  August Pua	Voltage - Primary	115V, 230V
Primary Winding(s)  Secondary Winding(s)  Dual  Center Tap  No  Power - Max  6 VA  Mounting Type  Through Hole  Termination Style  PC Pin  Size / Dimension  41.28mm L x 33.32mm W  Height - Seated (Max)  Voltage - Isolation  Dual  No  4200Vrms	Voltage - Secondary (Full Load)	Parallel 8V, Series 16V
Secondary Winding(s)DualCenter TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 33.32mm WHeight - Seated (Max)33.32mmVoltage - Isolation4200Vrms	Current - Output (Max)	Parallel 800mA, Series 400mA
Center TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 33.32mm WHeight - Seated (Max)33.32mmVoltage - Isolation4200Vrms	Primary Winding(s)	Dual
Power - Max 6 VA  Mounting Type Through Hole  Termination Style PC Pin  Size / Dimension 41.28mm L x 33.32mm W  Height - Seated (Max) 33.32mm  Voltage - Isolation 4200Vrms	Secondary Winding(s)	Dual
Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 33.32mm Voltage - Isolation 4200Vrms	Center Tap	No
Termination Style PC Pin  Size / Dimension 41.28mm L x 33.32mm W  Height - Seated (Max) 33.32mm  Voltage - Isolation 4200Vrms	Power - Max	6 VA
Size / Dimension 41.28mm L x 33.32mm W  Height - Seated (Max) 33.32mm  Voltage - Isolation 4200Vrms	Mounting Type	Through Hole
Height - Seated (Max)  Voltage - Isolation  33.32mm  4200Vrms	Termination Style	PC Pin
Voltage - Isolation 4200Vrms	Size / Dimension	41.28mm L x 33.32mm W
	Height - Seated (Max)	33.32mm
	Voltage - Isolation	4200Vrms
Weight 0.44 lb (199.58g)	Weight	0.44 lb (199.58g)
Report errors?		Report errors?

### FS16-400-C2-B Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## FS16-400-C2-B Payment Methods

































If you have any question about FS16-400-C2-B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com